

## Product information | TECHNICAL DATA SHEET

### WHITE GREASE

400 ml, 9.7 Oz, 275 g.

#### GENERAL DESCRIPTION

Multi-purpose grease with lubricating and antioxidant properties, suitable for all workshop jobs when a thorough and permanent lubrication is required. When applied in liquid, aerosol form, it effectively penetrates the insides of mechanical parts, lubricating them thoroughly and ensuring their perfect lubrication. Reduces wear thanks to the P.T.F.E. (Teflon) and increases longevity of all treated parts as well as the efficiency and performance of transmission systems.

It is very adherent, even on vertical surfaces due to its consistency which gives it its high concentration.

#### FEATURES

- Provides protection against corrosion.
- Easy to apply.
- Very good lubricity.
- Perfect adhesion.

#### APPLICATIONS

- Significantly reduces wear on bearings, chains, guide rails, cables, rims, etc...
- On hinges, locks, and mechanisms in general.
- Motors, machinery, automotive, industrial, cycling, etc...
- On guide rails and lift systems, etc...

#### INSTRUCTIONS FOR USE

- Never apply to equipment that is plugged in and use in well ventilated areas.
- Shake well before using. Apply in short sprays at a distance of 20 to 30 cm and spray the areas that need the most penetration from a closer distance.
- Move the mechanism gently while the solvent evaporates to aid the penetration process. The solvent evaporates quickly as the grease penetrates into the mechanism on which it has been applied.
- Request safety datasheets.

#### PHYSICAL PROPERTIES

Base:	Calcium Grease
Color:	Transparent white
Additives:	Antioxidants, P.T.F.E
Use temperature:	-10 a 100°C

\*Date last review: 12/03/2013

#### CAUTION



#### APPARENCE



#### LABEL



EX0141067 White Grease

#### CAP SYSTEM



#### PACKAGING

Nominal capacity 400 ml.  
Heat resistance of packaging: <50°C  
Propellant: GLP C<sub>3</sub>-C<sub>4</sub>.

Box (6 units)  
205 X 140 X 200 mm.

