

	<b>MATT WHITE BASE PRIMER</b> Code: AE0140910	
--	--	---

Version: 4 Revision: 02/12/2015



Previous revision: 21/05/2015

Date of printing: 02/12/2015


**SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**

1.1	<u>PRODUCT IDENTIFIER:</u>	MATT WHITE BASE PRIMER Code: AE0140910
1.2	<u>RELEVANT IDENTIFIED USES AND USES ADVISED AGAINST:</u> <u>Intended uses (main technical functions):</u> <span style="float: right;">[ ] Industrial [X] Professional [X] Consumers</span> # Surface priming. <u>Uses advised against:</u> This product is not recommended for any use or sector of use industrial, professional or consume other than those previously listed as 'Intended or identified uses'. If your use is not covered, please contact the supplier of this material safety data sheet. <u>Restrictions on manufacture, placing on market and use, according to Annex XVII of Regulation (EC) No. 1907/2006:</u> Not restricted.	
1.3	<u>DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET:</u> MONTANA COLORS, S.L. Pol. Ind. Pla de les Vives - c/AnaisNin 6 - E-08295 Sant Vicenç de Castellet (Barcelona) Phone: +34 93 8332760 - Fax: +34 93 8332761 <u>E-mail address of the person responsible for the safety data sheet:</u> e-mail: msds@montanacolors.com	
1.4	<u>EMERGENCY TELEPHONE NUMBER:</u>	+34 93 8332787 (9:00-17:00 h.) (working hours)

**SECTION 2 : HAZARDS IDENTIFICATION**

2.1	<u>CLASSIFICATION OF THE SUBSTANCE OR MIXTURE:</u>					
Classification in accordance with Regulation (EC) No. 1272/2008-487/2013 (CLP): DANGER: Flam. Aerosol 1:H222+H229   Eye Irrit. 2:H319   STOTSE (narcois) 3:H336   EUH066						
	<u>Danger class</u>	<u>Classification of the mixture</u>	<u>Cat.</u>	<u>Routes of exposure</u>	<u>Target organs</u>	<u>Effects</u>
	<u>Physicochemical:</u> 	Flam. Aerosol 1:H222+H229 Eye Irrit. 2:H319 STOT SE (narcois) 3:H336 EUH066	Cat.1 Cat.2 Cat.3 -	- Eyes Inhalation Skin	- Eyes CNS Skin	- Irritation Narcois Dryness, Cracking
	<u>Human health:</u> 					
	<u>Environment:</u> Not classified					

Full text of hazard statements mentioned is indicated in section 16.

2.2	<u>LABEL ELEMENTS:</u> 	This product is labelled with the signal word DANGER in accordance with Regulation (EC) No. 1272/2008-487/2013 (CLP)
	<u>Hazard statements:</u> H222 H229 H319 H336 EUH066	Extremely flammable aerosol. Pressurised container: may burst if heated. Causes serious eye irritation. May cause drowsiness or dizziness. Repeated exposure may cause skin dryness or cracking.
	<u>Precautionary statements:</u> P101 P102 P103 P210 P211 P251 P271-P260d P304+P340-P312 P305+P351+P338 P410+P412 P501a	If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Do not breathe aerosol. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Dispose of contents/container in a safe way.
	<u>Supplementary statements:</u> None. <u>Hazardous ingredients:</u> Ethyl acetate n-butyl acetate	

2.3	<u>OTHER HAZARDS:</u> Hazards which do not result in classification but which may contribute to the overall hazards of the mixture: <u>Other physicochemical hazards:</u> Vapours may form with air a mixture potentially flammable or explosive. <u>Other adverse human health effects:</u> No other relevant adverse effects are known. <u>Other negative environmental effects:</u> Does not contain substances that fulfil the PBT/vPvB criteria.
-----	---



**MATT WHITE BASE PRIMER**  
Code: AE0140910



**SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS**

3.1 SUBSTANCES:  
Not applicable (mixture).

3.2 MIXTURES:  
This product is a mixture.  
Chemical description:  
Aerosol.

HAZARDOUS INGREDIENTS:  
Substances taking part in a percentage higher than the exemption limit:

15 < 20 %	<b>Butane</b> CAS: 106-97-8 , EC: 203-448-7 CLP: Danger: Flam. Gas 1:H220   Press. Gas.:H280	Index No. 601-004-00-0 < CLP00
15 < 20 %	<b>Ethyl acetate</b> CAS: 141-78-6 , EC: 205-500-4 REACH: 01-2119475103-46 CLP: Danger: Flam. Liq. 2:H225   Eye Irrit. 2:H319   STOT SE (narcois) 3:H336   EUH066	Index No. 607-022-00-5 < REACH / ATP01
10 < 15 %	<b>n-butyl acetate</b> CAS: 123-86-4 , EC: 204-658-1 REACH: 01-2119485493-29 CLP: Warning: Flam. Liq. 3:H226   STOT SE (narcois) 3:H336   EUH066	Index No. 607-025-00-1 < REACH / ATP01
5 < 10 %	<b>Propane</b> CAS: 74-98-6 , EC: 200-827-9 CLP: Danger: Flam. Gas 1:H220   Press. Gas.:H280	Index No. 601-003-00-5 < CLP00
5 < 10 %	<b>Isobutane</b> CAS: 75-28-5 , EC: 200-857-2 CLP: Danger: Flam. Gas 1:H220   Press. Gas.:H280	Index No. 601-004-00-0 < CLP00
5 < 10 %	<b>Xylene (mixture of isomers)</b> CAS: 1330-20-7 , EC: 215-535-7 REACH: 01-2119488216-32 CLP: Danger: Flam. Liq. 3:H226   Acute Tox. (inh.) 4:H332   Acute Tox. (skin) 4:H312   Skin Irrit. 2:H315   Eye Irrit. 2:H319   STOT SE (irrit.) 3:H335   STOT RE 2:H373i   Asp. Tox. 1:H304	Index No. 601-022-00-9 < REACH

Impurities:  
# Does not contain other components or impurities which will influence the classification of the product.

Stabilizers:  
None

Reference to other sections:  
For more information on hazardous ingredients, see sections 8, 11, 12 and 16.

SUBSTANCES OF VERY HIGH CONCERN (SVHC):  
# List updated by ECHA on 15/06/2015.  
Substances SVHC subject to authorisation, included in Annex XIV of Regulation (EC) no. 1907/2006:  
None  
Substances SVHC candidate to be included in Annex XIV of Regulation (EC) no. 1907/2006:  
None




PERSISTENT, BIOACCUMULABLE AND TOXIC PBT, OR VERY PERSISTENT AND VERY BIOACCUMULABLE VPVB SUBSTANCES:  
Does not contain substances that fulfill the PBT/VPVB criteria.



**MATT WHITE BASE PRIMER**  
Code: AE0140910



**SECTION 4 : FIRST AID MEASURES**

4.1	<b>DESCRIPTION OF FIRST-AID MEASURES AND MAIN SYMPTOMS AND EFFECTS, ACUTE AND DELAYED:</b>	
4.2	 Symptoms may occur after exposure, so that in case of direct exposure to the product, when in doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. Lifeguards should pay attention to self-protection and use the recommended protective equipment if there is a possibility of exposure. Wear protective gloves when administering first aid.	
	<b>Route of exposure</b>	<b>Symptoms and effects, acute and delayed</b>
	<b>Inhalation:</b> 	Inhalation of solvent vapours may produce headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, unconsciousness.
	<b>Skin:</b>	In case of prolonged contact, the skin may become dry.
	<b>Eyes:</b> 	Contact with the eyes produces redness and pain.
	<b>Ingestion:</b>	If swallowed, may cause irritation of the throat, abdominal pain, drowsiness, nausea, vomiting and diarrhoea.
4.3	<b>INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED:</b> <b>Notes to physician:</b> Treatment should be directed at the control of symptoms and the clinical condition of the patient. <b>Antidotes and contraindications:</b> Specific antidote not known.	

**SECTION 5 : FIRE-FIGHTING MEASURES**

5.1	<b>EXTINGUISHING MEDIA:</b> Extinguishing powder or CO2. In the case of more important fires, also alcohol resistant foam and water spray/mist. Do not use for extinguishing: direct water jet. Direct water jet may not be effective to extinguish the fire, since the fire may spread.
5.2	<b>SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE:</b> Fire can produce a dense black smoke. As consequence of combustion or thermal decomposition, hazardous products may be produced: carbon monoxide, carbon dioxide. Irritant. Exposure to combustion or decomposition products may be a hazard to health.
5.3	<b>ADVICE FOR FIREFIGHTERS:</b> <b>Special protective equipment:</b> Depending on magnitude of fire, heat-proof protective clothing may be required, appropriate independent breathing apparatus, gloves, protective glasses or face masks and boots. If the fire-proof protective equipment is not available or not used, combat fire from a sheltered position or at a safe distance. The standard EN469 provides a basic level of protection for chemical incidents. <b>Other recommendations:</b> Cool with water the tanks, cisterns or containers close to sources of heat or fire. Bear in mind the direction of the wind. Do not allow fire-fighting residue to enter drains, sewers or water courses.

**SECTION 6 : ACCIDENTAL RELEASE MEASURES**

6.1	<b>PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES:</b> Eliminate possible sources of ignition and when appropriate, ventilate the area. Do not smoke. Avoid direct contact with this product. Avoid breathing vapours. Keep people without protection in opposition to the wind direction.
6.2	<b>ENVIRONMENTAL PRECAUTIONS:</b> Avoid contamination of drains, surface or subterranean water and soil. In the case of large scale spills or when the product contaminates lakes, rivers or sewages, inform the appropriate authorities in accordance with local regulations.
6.3	<b>METHODS AND MATERIAL FOR CONTAINMENT AND CLEANING UP:</b> Contain and mop up spills with non-combustible absorbent materials (earth, sand, vermiculite, diatomaceous earth, etc.). Avoid use of solvents. Keep the remains in a closed container.
6.4	<b>REFERENCE TO OTHER SECTIONS:</b> For contact information in case of emergency, see section 1. For information on safe handling, see section 7. For exposure controls and personal protection measures, see section 8. For subsequent waste disposal, follow the recommendations in section 13.



**MATT WHITE BASE PRIMER**  
Code: AE0140910



**SECTION 7 : HANDLING AND STORAGE**

**7.1 PRECAUTIONS FOR SAFE HANDLING:**  
Comply with the existing legislation on health and safety at work.  
General recommendations:  
Avoid any type of leakage or escape.  
Recommendations for the prevention of fire and explosion risks:  
Pressurised container. Protect from sunlight and do not expose to temperature exceeding 50°C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Do not smoke.  
- Flash point : # -82. °C  
- Autoignition temperature : # 405. °C  
- Upper/lower flammability or explosive limits : # 1.9 - 9.2 % Volume 25°C  
Recommendations for the prevention of toxicological risks:  
Do not eat, drink or smoke in application and drying areas. After handling, wash hands with soap and water. Avoid applying the product directly to people, animals, plants or foodstuffs. For exposure controls and personal protection measures, see section 8.  
Recommendations for the prevention of environmental contamination:  
It is not considered a danger to the environment. In the case of accidental spillage, follow the instructions indicated in section 6.

**7.2 CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES:**  
Prevent unauthorized access. Keep out of reach of children. This product should be stored isolated from heat and electrical sources. Do not smoke in storage area. If possible, avoid direct contact with sunlight. Avoid extreme humidity conditions. For more information, see section 10.  
Class of store : According to current legislation.  
Maximum storage period : 24. months  
Temperature interval : min: 5.°C, max: 50.°C (recommended).  
Incompatible materials:  
Keep away from oxidizing agents, from strongly alkaline and strongly acid materials.  
Type of packaging:  
According to current legislation.  
Limit quantity (Seveso III): Directive 96/82/EC~2003/105/EC:  
Lower threshold: 50 tons , Upper threshold: 200 tons

**7.3 SPECIFIC END USES:**  
For the use of this product do not exist particular recommendations apart from that already indicated.



MATT WHITE BASE PRIMER  
Code: AE0140910



**SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION**

**8.1 CONTROL PARAMETERS:**  
If a product contains ingredients with exposure limits, may be necessary a personnel monitoring, work place or biological, to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to EN689, EN14042 and EN482 standard concerning methods for assessing the exposure by inhalation to chemical agents, and exposure to chemical and biological agents. Reference should be also made to national guidance documents for methods for the determination of dangerous substances.

OCCUPATIONAL EXPOSURE LIMIT VALUES (TLV)

AGCIH 2013	Year	TLV-TWA		TLV-STEL		Remarks
		ppm	mg/m3	ppm	mg/m3	
Butane	2004	1000.	-	-	-	
Ethyl acetate	1996	400.	1440.	-	-	
n-butyl acetate	1998	150.	713.	200.	950.	
Propane	2004	1000.	-	-	-	
Isobutane	2004	1000.	-	-	-	
Xylene (mixture of isomers)	1996	100.	434.	150.	651.	A4

TLV - Threshold Limit Value, TWA - Time Weighted Average, STEL - Short Term Exposure Limit.  
A4 - Non classified as carcinogenic in humans.

BIOLOGICAL LIMIT VALUES:

Not established

DERIVED NO-EFFECT LEVEL (DNEL):

Derived no-effect level (DNEL) is a level of exposure that is considered safe, derived from toxicity data according to specific guidances included in REACH. DNEL values may differ from an occupational exposure limit (OEL) for the same chemical. OEL values may come recommended by a particular company, a government regulatory agency or an organization of experts. Although considered protective of health, the OEL values are derived by a process different of REACH.

<u>Derived no-effect level, workers:</u> - Systemic effects, acute and chronic: Ethyl acetate n-butyl acetate Xylene (mixture of isomers)	<u>DNEL Inhalation</u> mg/m3	<u>DNEL Cutaneous</u> mg/kg bw/d	<u>DNEL Oral</u> mg/kg bw/d
	1468. (a) 734. (c) 960. (a) 480. (c) 289. (a) 77.0 (c)	s/r (a) 63.0 (c) - (a) - (c) s/r (a) 180. (c)	- (a) - (c) - (a) - (c) - (a) - (c)
	<u>DNEL Inhalation</u> mg/m3	<u>DNEL Cutaneous</u> mg/cm2	<u>DNEL Eyes</u> mg/cm2
	1468. (a) 734. (c) 960. (a) 480. (c) 289. (a) s/r (c)	s/r (a) s/r (c) - (a) - (c) s/r (a) s/r (c)	b/r (a) - (c) - (a) - (c) - (a) - (c)
<u>Derived no-effect level, general population:</u> - Systemic effects, acute and chronic: Ethyl acetate n-butyl acetate Xylene (mixture of isomers)	<u>DNEL Inhalation</u> mg/m3	<u>DNEL Cutaneous</u> mg/kg bw/d	<u>DNEL Oral</u> mg/kg bw/d
	734. (a) 367. (c) 860. (a) 102. (c) 174. (a) 14.8 (c)	s/r (a) 37.0 (c) - (a) - (c) s/r (a) 108. (c)	s/r (a) 4.50 (c) - (a) - (c) s/r (a) 1.60 (c)
	<u>DNEL Inhalation</u> mg/m3	<u>DNEL Cutaneous</u> mg/cm2	<u>DNEL Eyes</u> mg/cm2
	734. (a) 367. (c) 860. (a) 102. (c) 174. (a) s/r (c)	s/r (a) s/r (c) - (a) - (c) s/r (a) s/r (c)	- (a) - (c) - (a) - (c) - (a) - (c)

(a) - Acute, short-term exposure, (c) - Chronic, long-term or repeated exposure.  
(-) - DNEL not available (without data of registration REACH).  
s/r - DNEL not derived (not identified hazard).  
b/r - DNEL not derived (low hazard).



**MATT WHITE BASE PRIMER**  
Code: AE0140910



PREDICTED NO-EFFECT CONCENTRATION (PNEC):

<u>Predicted no-effect concentration, aquatic organisms:</u> - Fresh water, marine water and intermitent release: Ethyl acetate n-butyl acetate Xylene (mixture of isomers)	<u>PNEC Fresh water</u> mg/l 0.260 0.180 0.327	<u>PNEC Marine</u> mg/l 0.0260 0.0180 0.327	<u>PNEC Intermittent</u> mg/l 1.65 0.360 0.327
	<u>PNEC STP</u> mg/l 650. 35.6 6.58	<u>PNEC Sediments</u> mg/kg dry weight 1.25 0.981 12.5	<u>PNEC Sediments</u> mg/kg dry weight 0.125 0.0981 12.5
<u>Predicted no-effect concentration, terrestrial organisms:</u> - Air, soil and effects for predators and humans: Ethyl acetate n-butyl acetate Xylene (mixture of isomers)	<u>PNEC Air</u> mg/m3 - - -	<u>PNEC Soil</u> mg/kg dry weight 0.240 0.0903 2.31	<u>PNEC Oral</u> mg/kg bw/d 200. - -

(-) - PNEC not available (without data of registration REACH).

8.2

EXPOSURE CONTROLS:

ENGINEERING MEASURES:



Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these measures are not sufficient to maintain concentrations of particulates and vapours below the Occupational Exposure Limits, suitable respiratory protection must be worn.

Protection of respiratory system: Avoid the inhalation of vapours.

Protection of eyes and face: It is recommended to dispose of water taps or sources with clean water close to the working area.

Protection of hands and skin: It is recommended to dispose of water taps or sources with clean water close to the working area. Barrier creams may help to protect the exposed areas of the skin. Barrier creams should not be applied once exposure has occurred.

OCUPATIONAL EXPOSURE CONTROLS: Directive 89/686/EEC~96/58/EC:

As a general measure on prevention and safety in the work place, we recommend the use of a basic personal protection equipment (PPE), with the corresponding EC marking. For more information on personal protective equipment (storage, use, cleaning, maintenance, type and characteristics of the PPE, protection class, marking, category, CEN norm, etc.), you should consult the informative brochures provided by the manufacturers of PPE.

<u>Mask:</u> 	Suitable combined filter mask for gases, vapours and particles (EN14387/EN143). Classe 1: low capacity up to 1000 ppm, Classe 2: medium capacity up to 5000 ppm, Classe 3: high capacity up to 10000 ppm. In order to obtain a suitable protection level, the filter class must be selected depending on the type and concentration of the contaminating agents present, in accordance with the specifications supplied by the filter producers. The respiratory equipment with filters does not work satisfactorily when the air contains high concentrations of vapour or oxygen content less than 18% in volume.
<u>Goggles:</u> 	Safety goggles with suitable lateral protection (EN166). Clean daily and disinfect at regular intervals in accordance with the instructions of the manufacturer.
<u>Face shield:</u>	No.
<u>Gloves:</u> 	Gloves resistant against chemicals (EN374). There are several factors (for example, temperature), they do in practice the period of use of a protective gloves resistant against chemicals is clearly lower than the established standard EN374. Due to the wide variety of circumstances and possibilities, we must have in mind the manual of instructions from manufacturers of gloves. The gloves should be immediately replaced when any sign of degradation is noted.
<u>Boots:</u>	No.
<u>Apron:</u>	No.
<u>Clothing:</u>	No.

Thermal hazards:

Not applicable (the product is handled at room temperature).

ENVIRONMENTAL EXPOSURE CONTROLS:

Avoid any spillage in the environment. Avoid any release into the atmosphere.

Spills on the soil: Prevent contamination of soil.

Spills in water: Do not allow to escape into drains, sewers or water courses.

Emissions to the atmosphere: Because of volatility, emissions to the atmosphere while handling and use may result. When possible, avoid solvent release to the atmosphere; do not pulverize more than is strictly necessary.

VOC (industrial installations): If this product is used in an industrial installation, it must be verified if it is applicable the Directive 1999/13/EC, on the limitation of emissions of volatile compounds due to the use of organic solvents in certain activities and installations: Solvents : 70.9% Weight , VOC (supply) : 70.9% Weight , VOC : 51.3% C (expressed as carbon) , Molecular weight (average) : 78.1 , Number C atoms (average) : 4.7.



MATT WHITE BASE PRIMER  
Code: AE0140910



**SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES**

9.1	<p><b>INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES:</b></p> <p><u>Appearance</u></p> <ul style="list-style-type: none"> <li>- Physical state : Aerosol.</li> <li>- Colour : White.</li> <li>- Odour : Characteristic</li> <li>- Odour threshold : Not available (mixture).</li> </ul> <p><u>pH-value</u></p> <ul style="list-style-type: none"> <li>- pH : Not applicable</li> </ul> <p><u>Change of state</u></p> <ul style="list-style-type: none"> <li>- Melting point : Not applicable (mixture).</li> <li>- Initial boiling point : Not applicable</li> </ul> <p><u>Density</u></p> <ul style="list-style-type: none"> <li>- Relative density : # 0.889 at 20/4°C Relative water</li> </ul> <p><u>Stability</u></p> <ul style="list-style-type: none"> <li>- Decomposition temperature : # Not available</li> </ul> <p><u>Viscosity:</u></p> <ul style="list-style-type: none"> <li>- Viscosity (flow time) : Not applicable</li> </ul> <p><u>Volatility:</u></p> <ul style="list-style-type: none"> <li>- Vapour pressure : Not available</li> </ul> <p><u>Solubility(ies)</u></p> <ul style="list-style-type: none"> <li>- Solubility in water: : Not miscible</li> <li>- Solubility in oils and fats: : Not applicable</li> </ul> <p><u>Flammability:</u></p> <ul style="list-style-type: none"> <li>- Flash point : # -82. °C</li> <li>- Upper/lower flammability or explosive limits : # 1.9 - 9.2 % Volume 25°C</li> <li>- Autoignition temperature : # 405. °C</li> </ul> <p><u>Explosive properties:</u> Vapours can form explosive mixtures with air and are able to flame up or explode in presence of an ignition source.</p> <p><u>Oxidizing properties:</u> Not classified as oxidizing product.</p>
-----	---

9.2	<p><b>OTHER INFORMATION:</b></p> <ul style="list-style-type: none"> <li>- Heat of combustion : # 7062. Kcal/kg</li> <li>- Solids : 29.1 % Weight</li> <li>- VOC (supply) : 70.9 % Weight</li> <li>- VOC (supply) : # 630.2 g/l</li> </ul> <p>The values indicated do not always coincide with product specifications. The data for the product specifications can be found in the technical data sheet of the same. For additional information concerning physical and chemical properties related to safety and environment, see sections 7 and 12.</p>
-----	--

**SECTION 10 : STABILITY AND REACTIVITY**

10.1	<p><b>REACTIVITY:</b></p> <p><u>Corrosivity to metals:</u> It is not corrosive to metals.</p> <p><u>Pyrophorical properties:</u> It is not pyrophoric.</p>
10.2	<p><b>CHEMICAL STABILITY:</b></p> <p>Stable under recommended storage and handling conditions.</p>
10.3	<p><b>POSSIBILITY OF HAZARDOUS REACTIONS:</b></p> <p>Possible dangerous reaction with oxidizing agents, acids, alkalis, amines, peroxides.</p>
10.4	<p><b>CONDITIONS TO AVOID:</b></p> <p><u>Heat:</u> Keep away from sources of heat.</p> <p><u>Light:</u> Avoid direct contact with sunlight.</p> <p><u>Air:</u> Not applicable.</p> <p><u>Humidity:</u> Avoid extreme humidity conditions.</p> <p><u>Pressure:</u> Not applicable.</p> <p><u>Shock:</u> Not applicable.</p>
10.5	<p><b>INCOMPATIBLE MATERIALS:</b></p> <p>Keep away from oxidizing agents, from strongly alkaline and strongly acid materials.</p>
10.6	<p><b>HAZARDOUS DECOMPOSITION PRODUCTS:</b></p> <p>As consequence of thermal decomposition, hazardous products may be produced: carbon monoxide.</p>



MATT WHITE BASE PRIMER  
Code: AE0140910



**SECTION 11 : TOXICOLOGICAL INFORMATION**

No experimental toxicological data on the preparation is available. The toxicological classification for these mixture has been carried out by using the conventional calculation method of the Regulation (EC) No. 1272/2008~487/2013 (CLP).

11.1 INFORMATION ON TOXICOLOGICAL EFFECTS:

ACUTE TOXICITY:

Dose and lethal concentrations for individual ingredients:	DL50 (OECD 401) mg/kg oral	DL50 (OECD 402) mg/kg cutaneous	CL50 (OECD 403) mg/m3.4h inhalation
Butane			> 100000 Rat
Ethyl acetate	5620. Rat	18000. Rabbit	> 44000. Rat
n-butyl acetate	10768. Rat	17600. Rabbit	> 23400. Rat
Xylene (mixture of isomers)	4300. Rat	1700. Rabbit	> 22080. Rat

No observed adverse effect level

Not available

Lowest observed adverse effect level

Not available

INFORMATION ON LIKELY ROUTES OF EXPOSURE : Acute toxicity:

Routes of exposure	Acute toxicity	Cat.	Main effects, acute and/or delayed
<u>Inhalation:</u> Not classified	ETA > 20000 mg/m3	-	Not classified as a product with acute toxicity if inhaled (based on available data, the classification criteria are not met).
<u>Skin:</u> Not classified	ETA > 2000 mg/kg	-	Not classified as a product with acute toxicity in contact with skin (based on available data, the classification criteria are not met).
<u>Eyes:</u> Not classified	Not available	-	Not classified as a product with acute toxicity by eye contact (lack of data).
<u>Ingestion:</u> Not classified	ETA > 5000 mg/kg	-	Not classified as a product with acute toxicity if swallowed (based on available data, the classification criteria are not met).

CORROSION / IRRITATION / SENSITISATION :

Danger class	Target organs	Cat.	Main effects, acute and/or delayed
<u>Respiratory corrosion/irritation:</u> Not classified	-	-	Not classified as a product corrosive or irritant by inhalation (based on available data, the classification criteria are not met).
<u>Skin corrosion/irritation:</u> Not classified	-	-	Not classified as a product corrosive or irritant in contact with skin (based on available data, the classification criteria are not met).
<u>Serious eye damage/irritation:</u> 	Eyes 	Cat.2	IRRITANT: Causes serious eye irritation.
<u>Respiratory sensitisation:</u> Not classified	-	-	Not classified as a product sensitising by inhalation (based on available data, the classification criteria are not met).
<u>Skin sensitisation:</u> Not classified	-	-	Not classified as a product sensitising by skin contact (based on available data, the classification criteria are not met).

ASPIRATION HAZARD:

Danger class	Target organs	Cat.	Main effects, acute and/or delayed
<u>Aspiration hazard:</u> Not classified	-	-	Not applicable.

SPECIFIC TARGET ORGANS TOXICITY (STOT) : Single exposure (SE) and/or Repeated exposure (RE):

Effects	SE/RE	Target organs	Cat.	Main effects, acute and/or delayed
<u>Cutaneous:</u>	RE	Skin 	-	DEFATTENING: Repeated exposure may cause skin dryness or cracking.
<u>Neurological:</u> 	SE	CNS 	Cat.3	NARCOTIC: May cause drowsiness or dizziness if inhaled.





MATT WHITE BASE PRIMER  
Code: AE0140910



**CMR EFFECTS:**

**Carcinogenic effects:** Is not considered as a carcinogenic product.  
**Genotoxicity:** Is not considered as a mutagenic product.  
**Toxicity for reproduction:** Do not harm fertility. Do not harm the fetus developing.  
**Effects via lactation:** Not classified as a hazardous product for children breast-fed.

**DELAYED AND IMMEDIATE EFFECTS AS WELL AS CHRONIC EFFECTS FROM SHORT AND LONG-TERM EXPOSURE:**

**Routes of exposure:** May be absorbed by inhalation of vapour, through the skin and by ingestion.  
**Short-term exposure:** Exposure to solvent vapour concentrations in excess of the stated occupational exposure limit, may result in adverse health effects, such as mucous membrane and respiratory system irritation and adverse effects on kidneys, liver and central nervous system. Liquid splashes in the eyes may cause irritation and reversible damage. If swallowed, may cause irritation of the throat; other effects may be the same as described in the exposure to vapours.  
**Long-term or repeated exposure:** Repeated or prolonged contact may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin. Repeated exposure may cause skin dryness or cracking.

**INTERACTIVE EFFECTS:**

Not available.

**INFORMATION ABOUT TOXICOCINETICS, METABOLISM AND DISTRIBUTION:**

**Dermal absorption:** Not available.  
**Basic toxicokinetics:** Not available.

**ADDITIONAL INFORMATION:**

Not available.

**SECTION 12 : ECOLOGICAL INFORMATION**

No experimental ecotoxicological data on the preparation as such is available. The ecotoxicological classification for these mixture has been carried out by using the conventional calculation method of the Regulation (EC) No. 1272/2008-487/2013 (CLP).

12.1	<b>TOXICITY:</b>			
	<b>Acute toxicity in aquatic environment for individual ingredients :</b> Ethyl acetate n-butyl acetate Xylene (mixture of isomers)	<b>CL50 (OECD 203)</b> mg/L.96hours 212. Fishes 18. Fishes 14. Fishes	<b>CE50 (OECD 202)</b> mg/L.48hours 164. Daphnia 44. Daphnia 16. Daphnia	<b>CE50 (OECD 201)</b> mg/L.72hours > 100. Algae 675. Algae > 10. Algae
	<b>No observed effect concentration</b> n-butyl acetate	<b>NOEC (OECD 210)</b> mg/L.28days	<b>NOEC (OECD 211)</b> mg/L.21days 23. Daphnia	
	<b>Lowest observed effect concentration</b> Not available			
12.2	<b>PERSISTENCE AND DEGRADABILITY:</b> Not available.			
	<b>Aerobic biodegradation for individual ingredients :</b> Butane Ethyl acetate n-butyl acetate Propane Isobutane Xylene (mixture of isomers)	<b>DQO</b> mgO2/g 3577. 1540. 2204. 3629. 3577. 2620.	<b>%DBO/DQO</b> 5 days 14 days 28 days ~ 62. ~ 69. ~ 94. ~ 80. ~ 82. ~ 83.	<b>Biodegradability</b> Easy Easy Easy Easy Not available Easy
12.3	<b>BIOACCUMULATIVE POTENTIAL:</b> Not available.			
	<b>Bioaccumulation for individual ingredients :</b> Butane Ethyl acetate n-butyl acetate Propane Isobutane Xylene (mixture of isomers)	<b>logPow</b> 0.730 1.81 2.36 3.16	<b>BCF</b> L/kg 3.2 (calculated) 6.9 (calculated) 57. (calculated)	<b>Potential</b> No bioaccumulable No bioaccumulable No bioaccumulable Not available Not available Low
12.4	<b>MOBILITY IN SOIL:</b> Not available.			
12.5	<b>RESULTS OF PBT AND VPV B ASSESSMENT:</b> Annex XIII of Regulation (EC) no. 1907/2006: Does not contain substances that fulfill the PBT/vPvB criteria.			
12.6	<b>OTHER ADVERSE EFFECTS:</b> <b>Ozone depletion potential:</b> Not available. <b>Photochemical ozone creation potential:</b> Not available. <b>Earth global warming potential:</b> In case of fire or incineration liberates CO2. <b>Endocrine disrupting potential:</b> Not available.			



MATT WHITE BASE PRIMER  
Code: AE0140910

**SECTION 13 : DISPOSAL CONSIDERATIONS****13.1** WASTE TREATMENT METHODS: [Directive 2008/98/EC:](#)

Take all necessary measures to prevent the production of waste whenever possible. Analyse possible methods for revaluation or recycling. Do not discharge into drains or the environment, dispose of at an authorised waste collection point. Waste should be handled and disposed of in accordance with current local and national regulations. For exposure controls and personal protection measures, see section 8.

Disposal of empty containers: [Directive 94/62/EC~2005/20/EC, Decision 2000/532/EC:](#)

Emptied containers and packaging should be disposed of in accordance with currently local and national regulations. The classification of packaging as hazardous waste will depend on the degree of emptying of the same, being the holder of the residue responsible for their classification, in accordance with Chapter 15 01 of Decision 2000/532/EC, and forwarding to the appropriate final destination. With contaminated containers and packaging, adopt the same measures as for the product in itself. Ensure the container is completely empty before throwing it away.

Procedures for neutralising or destroying the product:

In accordance with local regulations. Do not incinerate closed containers.



MATT WHITE BASE PRIMER  
Code: AE0140910



**SECTION 14 : TRANSPORT INFORMATION**

14.1	<u>UN NUMBER:</u> 1950
14.2	<u>UN PROPER SHIPPING NAME:</u> AEROSOLS
14.3 14.4	<p><u>TRANSPORT HAZARD CLASS(ES) AND PACKING GROUP:</u></p> <p><u>Transport by road (ADR 2015) and Transport by rail (RID 2015):</u></p> <ul style="list-style-type: none"> <li>- Class: 2</li> <li>- Packaging group: -</li> <li>- Classification code: 5F</li> <li>- Tunnel restriction code: (D)</li> <li>- Transport category: 2 , max. ADR 1.1.3.6. 333 L</li> <li>- Limited quantities: LQ2 (see total exemptions ADR 3.4)</li> <li>- Transport document: Consignment paper.</li> <li>- Instructions in writing: ADR 5.4.3.4</li> </ul> <p><u>Transport by sea (IMDG 36-12):</u></p> <ul style="list-style-type: none"> <li>- Class: 2</li> <li>- Packaging group: -</li> <li>- Emergency Sheet (EmS): F-D,S-U</li> <li>- First Aid Guide (MFAG): 620*</li> <li>- Marine pollutant: No.</li> <li>- Transport document: Shipping Bill of lading.</li> </ul> <p><u>Transport by air (ICAO/IATA 2014):</u></p> <ul style="list-style-type: none"> <li>- Class: 2</li> <li>- Packaging group: -</li> <li>- Transport document: Air Bill of lading.</li> </ul> <p><u>Transport by inland waterways (ADN):</u> Not available.</p>
14.5	<u>ENVIRONMENTAL HAZARDS:</u> Not applicable (not classified as hazardous for the environment).
14.6	<u>SPECIAL PRECAUTIONS FOR USER:</u> Ensure that persons transporting the product know what to do in case of accident or spill. Always transport in closed containers that are in a vertical position and sure. Ensure adequate ventilation.
14.7	<u>TRANSPORT IN BULK ACCORDING TO ANNEX II OF MARPOL 73/78 AND THE IBC CODE:</u> Not applicable.

**SECTION 15 : REGULATORY INFORMATION**

15.1	<p><u>EU SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS/LEGISLATION SPECIFIC:</u> The regulations applicable to this product generally are listed throughout this material safety data sheet.</p> <p><u>Restrictions on manufacture, placing on market and use:</u> See section 1.2</p> <p><u>Control of the risks inherent in major accidents (Seveso III):</u> See section 7.2</p> <p><u>Tactile warning of danger:</u> Not applicable (the classification criteria are not met).</p> <p><u>Child safety protection:</u> Not applicable (the classification criteria are not met).</p> <p><u>Legislación específica sobre aerosoles:</u> It is applicable the Directive 75/324/EEC~2013/10/EU, relating to aerosol dispensers and the Directive 87/404/EEC, concerning simple pressure packages.</p> <p><u>OTHER REGULATIONS:</u> Not available</p>
15.2	<p><u>CHEMICAL SAFETY ASSESSMENT:</u> # For this mixture has not been carried out a chemical safety assessment.</p>



MATT WHITE BASE PRIMER  
Code: AE0140910



## SECTION 16 : OTHER INFORMATION

16.1 [TEXT OF THE PHRASES AND NOTES REFERENCED IN SECTIONS 2 AND/OR 3:](#)  
[Hazard statements according the Regulation \(EC\) No. 1272/2008-487/2013 \(CLP\), Annex III:](#)  
H220 Extremely flammable gas. H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour. H280 Contains gas under pressure: may explode if heated. H304 May be fatal if swallowed and enters airways. H312 Harmful in contact with skin. H315 Causes skin irritation. H319 Causes serious eye irritation. H332 Harmful if inhaled. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. EUH066 Repeated exposure may cause skin dryness or cracking. H373i May cause damage to organs through prolonged or repeated exposure if inhaled.

[ADVICES ON ANY TRAINING APPROPRIATE FOR WORKERS:](#)

It is recommended for all staff that will handle this product to carry out a basic training in occupational risk and prevention, in order to provide understanding and interpretation of material safety data sheets and labelling of products as well.

[MAIN LITERATURE REFERENCES AND SOURCES FOR DATA:](#)

- European Chemicals Agency: ECHA, <http://echa.europa.eu/>
- Access to European Union Law, <http://eur-lex.europa.eu/>
- Industrial Solvents Handbook, Ibert Mellan (Noyes Data Co., 1970).
- Threshold Limit Values, (AGCIH, 2013).
- European agreement on the international carriage of dangerous goods by road, (ADR 2015).
- International Maritime Dangerous Goods Code IMDG including Amendment 36-12 (IMO, 2012).

[ABBREVIATIONS AND ACRONYMS:](#)

List of abbreviations and acronyms that can be used (but not necessarily used) in this material safety data sheet:

- REACH: Regulation concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals.
- DSD: Dangerous Substances Directive.
- DPD: Dangerous Preparations Directive.
- GHS: Globally Harmonized System of Classification and Labelling of Chemicals of the United Nations.
- CLP: European regulation on Classification, Labelling and Packaging of substances and chemical mixtures.
- EINECS: European Inventory of Existing Commercial Chemical Substances.
- ELINCS: European List of Notified Chemical Substances.
- CAS: Chemical Abstracts Service (Division of the American Chemical Society).
- UVCB: Substances of Unknown or Variable composition, complex reaction products or biological materials).
- SVHC: Substances of Very High Concern.
- PBT: Persistent, bioaccumulable and toxic substances.
- vPvB: Very persistent and very bioaccumulable substances.
- VOC: Volatile Organic Compounds.
- DNEL: Derived No-Effect Level (REACH).
- PNEC: Predicted No-Effect Concentration (REACH).
- LD50: Letaal dose, 50 percent.
- LC50: Letaal concentration, 50 percent.
- UN: United Nations Organisation.
- ADR: European agreement concerning the international carriage of dangerous goods by road.
- RID: Regulations concerning the international transport of dangerous goods by rail.
- IMDG: International Maritime code for Dangerous Goods.
- IATA: International Air Transport Association.
- ICAO: International Civil Aviation Organization.

[MATERIAL SAFETY DATA SHEET REGULATIONS:](#)

# *Material Safety Data Sheet in accordance with Article 31 of Regulation (EC) No. 1907/2006 (REACH) and Annex of Regulation (EU) No. 2015/830.*

[HISTORY:](#)[Revision:](#)

Version: 3                      21/05/2015

Version: 4                      02/12/2015

[Modifications with respect to the previous Material Safety Data Sheet:](#)

# *The possible legislative, contextual, numerical, methodological and normative changes with respect to the previous version are highlighted in this Material Safety Data Sheet by a mark # in red and italic.*

The information of this Material Safety Data Sheet, is based on the present state of knowledge and on current UE and national laws, as the users' working conditions are beyond our knowledge and control. The product is not to be used for other purposes than those specified, without first obtaining written handling instruction. It is always the responsibility of the user to take all necessary steps in order to fulfil the demand laid down in the local rules and legislation. The information in this Material Safety Data Sheet is meant as a description of the safety requirements of the product and it is not to be considered as a guarantee of the product's properties.