

Product information | TECHNICAL DATA SHEET

MEGA COLORS. Solid Colors. Glossy paint, higher pressure, best opacity and high powered.
600 ml, 15.5 Oz, 440 g.

GENERAL DESCRIPTION

Alkyd gloss enamel, formulated with high quality pigments and with a very fast drying action. It leverages the power of the valve to spray the paint at high speed, obtaining a much wider span and a more fluid coat of paint. For a perfect finish with very good colour retention and weather resistance.

FEATURES

- High pressure.
- Very fast drying.
- Excellent flexibility.
- Easy to apply and repaint.
- Good hardening.
- Does not contain lead nor other heavy metals.
- High covering capability.
- Good resistance to the outdoors.
- Color and brightness durability.
- Good resistance to UV light (see chart).
- Strong resistance to scratching once the film is polymerized.

INSTRUCTIONS FOR USE

- Shake the aerosol well before using, approximately for one minute after hearing the sound of the mixer.
- Apply to clean, dry surfaces. On rusty metallic surfaces remove rust with a wire brush and prepare an anti-rust primer if considered necessary.
- For best results apply in thin layers. Three thin layers are always better than one thick one, and may be repainted within fifteen minutes with the same paint.
- Turn the aerosol upside down to clean out the valve after use, if the nozzle becomes blocked replace it with a new one.
- Never apply to equipment that is plugged in and use in well ventilated areas.
- Request safety datasheets.

PHYSICAL PROPERTIES

High pressure:	Fast female valve
Propulseur:	Butane / Propane / Mix
Type de liant:	Modified alkyd
Color:	See Chart
Shine 60° (ASTM D-523 ISO 2813):	60-90
Dry to the touch (ASTM D-1640 ISO 1517):	15'
Completely dry (ASTM D-1640 ISO 1517):	24 h
Thickness of dry layer (ASTM D-823 ISO 2808):	15 micras/capa
Adherence (ASTM D-3359 ISO 2409):	3 B
Theoretical yield (continuous painting):	5,75 m ² to 600 ml
Thinner:	Mix
Product life:	(Well Stored) 10 years
Condition for application:	Minimum room temperature 8°C Surface temperature 5°C a 50°C Max humidity 85% R.H.P
Heat resistance of paint:	100°C
Repintado:	After 15'

* All of the adherence tests have been carried out on iron plates.

APPLICATIONS

Owing to the product's characteristics, the recommended use is for retouches and painting on all types of materials, whether for domestic uses, crafts, fine arts, or ultimately for anything which requires the properties found in a high-quality spray paint.

- Graffiti y Muralismo
- Jardinería
- Bellas artes
- Signage
- Bricolaje

APPARENCE



LABEL



CAP SYSTEM



COLORS

 EX0161021 Light Yellow	 EX0160219 Paris Green	 EX0160225 Geisha Violet
 EX0162003 Pastel Orange	 EX0160034 Guacamole Green	 EX0160216 Anonymous Violet
 EX0163020 Light Red	 EX0160008 Light Blue	 EX0169010 White
 EX0164010 Magenta	 EX0160030 Electric Blue	 EX0169011 Black

CAUTION



PACKAGING

High pressure.
Heat resistance of packaging: <50°C
Propellant: GLP – HC C₃-C₄
Nominal capacity: 600 ml.

Box (6 units)
200 X 280 X 140 mm.



Due to technical reasons this color chart might not reproduce the real colors. For accurate color reference see the spray can's Donut. © Montana Colors 2016.