STAIN COVERAGE.
500 ml, 15 Oz, 420 g.

GENERAL DESCRIPTION

Painting made with high quality acrylic resins together with titanium dioxide and additives to obtain a painting with a high covering power, ideal for covering tough stains in a fast and durable manner.

FEATURES

- Fast drying.
- White matt.
- Good adherence.
- Good covering power.
- Does not contain lead and other heavy metals.
- Easy to apply and recoat.
- High colour durability.
- Non-yellowing.

APPLICATIONS

Due to the characteristics of the product, we recommend its use for final finishing or as a background layer for other paintings.

- DIY
- Handicrafts
- Industrial applications
- Domestic

INSTRUCTIONS FOR USE

- Shake can vigorously for one minute after hearing mixer noise.
- Apply to clean, dry surfaces. On rusty metallic surfacesemove rust with a wire brush.Apply an anchor layer on plastics and polyesters.
- For best results apply in thin layers. Three thin layers are always better than one thick one, and may be repainted within five minutes with the same paint.
- After use, turn the aerosol upside down to clean out the valve. If the nozzle becomes blocked replace it with a new one
- Disconnect the electrical appliance before painting
- Use it in well ventilated areas
- Request safety data sheets

PHYSICAL PROPERTIES

Brinder type:	Thermoplastic acrylic
Color:	White
Brightness:	<10%
Dry to the touch (ASTM D-1640 ISO 1517):	5'
Total drying (ASTM D-1640 ISO 1517):	20'
Thickness of the dry coat:	20 µ/capa (2 applications)
theoretical Coverage (pintado en continuo):	3 m²
Solvent:	Butyl Acetate
Product life:	>2 years
Recoating:	After 5'
Paint heat resistance:	160ºC
Application conditions:	Tº environment min. 8ºC
	Tº Surface min 5-50ºC
	Humidity max. 85% R.H.P

* Adherence tests were performed on steel.

CAUTION

APPARENCE

DONUT
Indicates the paint color

LID
Protects the valve and the nozzle.

240 mm.

65 mm.

LABEL

Nombre del color
Color name
REF. N#
COD. BARRAS/BAR CODE
Nº EX
Lote fabricación
Envasado / Caducidad

EX0150987   Stain coverage

CAP SYSTEM

PACKAGING

Nominal Capacity: 500 ml
Container heat resistance: <50ºC
Propellant: DME

Box (6 units)
205 X 140 X 200 mm.

Management System
ISO 9001:2008
ISO 14001:2004

TÜVRheinland CERTIFIED
www.tuv.com
ID 9109026640

Company certified according to quality standard
ISO 9001:2000
ISO 14001:2004
Made in Europe.