

## Product information | TECHNICAL DATA SHEET

### GREY FILLER.

400 ml, 11 Oz, 318 g.

#### GENERAL DESCRIPTION

Highly thick primer paint "Filler Primer" monocomponent manufactured with a modified nitro alkyd resins that allow for excellent recoatability. d. Primer filler can be used on primers, polyester putty, or directly on sanded down panels to obtain a filling and leveling effect on the surface.

#### FEATURES

- Fast drying.
- High filling power.
- Easy to sand down.
- It does not contain lead or other heavy metals.
- Easy to apply and recoat.

#### APPLICATIONS

Primer filler can be used on primers, polyester putty or directly on sanded down panels.

- Industry
- Automotive industry

#### INSTRUCTIONS FOR USE

- For professional use only.
- Shake the aerosol well before using, approximately for one minute after hearing the sound of the mixer.
- For best results apply in thin layers. Three thin layers are always better than one thick one, and may be repainted within 20 minutes with the same paint.
- Do not apply on thermoplastic acrylic enamels. For panel: degreases and removes rust. On 2C Polyester putty: apply directly on to sanded down surface
- Turn the aerosol upside down to clean out the valve after use. If te nozzle becomes blocked replace it with a new one.
- Never apply to equipment that is plugged in and use in well ventilated areas.
- Request safety datasheets.

#### PHYSICAL PROPERTIES

Binder type:	Nitrosintético
Color:	Grey
Shine 60°:	<10%
Dry to the touch (ASTM D-1640 ISO 1517):	10'
Total drying (ASTM D-1640 ISO 1517):	2h
Theoretical yield (continuous painting):	2 m <sup>2</sup>
Thinner:	Butyl Acetate
Product life:	>2 Years
Recoating:	After 10'
Condition for application:	T° environment min. 8°C
	T° surface min. 5-50°C
	Humidity Max. 85% R.H.P

\* Adherence tests were performed on steel.

#### ATENCIÓN



#### APPARENCE

##### DONUT

Indicates the paint color.

##### LID

Protects the valve and the nozzle.



#### LABEL



EX0140954 Grey Filler

#### CAP SYSTEM



Transversal Cap  
Fino - Thin

#### PACKAGING

Nominal capacity 400 ml.  
Heat resistance of packaging: <50°C  
Propellant: DME

Box (6 units)  
205 X 140 X 200 mm.

