

Product information | TECHNICAL DATA SHEET

ANTI RUST PRIMER

400 ml: 11 Oz, 305 g.

GENERAL DESCRIPTION

Anti rust primer formulated with acrylic resins and corrosion inhibitor pigments, makes it ideal for protecting any iron surface.

FEATURES

- Fast drying.
- Good elasticity.
- Easy of application and recoating.
- Good adherence.
- Does not contain lead.
- High covering power.
- Very high resistance to outdoor exposure.
- High anti-corrosion power.

APPLICATIONS

Suitable as primer in spray paint systems. Its anticorrosive power makes it ideal as a primer coat for protecting any iron surface.

- Automotive industry
- Industrial applications
- Metal structures
- DIY
- Mantenimiento

INSTRUCTIONS FOR USE

- Shake can vigorously for one minute after hearing mixer noise.
- Thoroughly clean, degrease, and dry the object to be painted. On rusty metallic surfaces, remove corrosion using a wire brush.
- Apply thin coats for best results, always thin layers is better than one thick, paintable after ten minutes with the same paint.
- Disconnect the electrical appliance before painting. Use it in well ventilated areas.
- Request safety data sheets.

PHYSICAL PROPERTIES

Brinder type:	Acrylic
Color:	Gray, Red
Dry to the touch (ASTM D-1640 ISO 1517):	10'
Total drying (ASTM D-1640 ISO 1517):	30'
Thickness of dry layer (ASTM D-823 ISO 2808):	15 µ/layer
Adherence (ASTM D-3359 ISO 2409):	B
Theoretical Coverage (pintado en continuo):	2,5 m² for 400 ml 0,70 m² for 150 ml
Thinner:	Butyl Acetate
Product life:	>5 Years
Recoating:	After 10'
Painted resistance to heat:	160°C
Applocation conditions:	T° environment min 8°C T° surface min 5-50°C Humidity max 85% R.H.P

*Adherence tests were performed on steel.

ATENCIÓN



APPARENCE



LABEL



EX0140115 Imp. Antiox. Gris

EX0140131 Imp. Antiox. Roja

CAP SYSTEM



PACKAGING

Nominal capacity 400 ml.
Heat resistance of packaging: <50°C
Propellant: DME

Box (6 units)
205 X 140 X 200 mm.

