



SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

- 1.1 Product identifier:** EX014H0101 - MTN HARDCORE SILVER
Other means of identification:
Non-applicable
- 1.2 Relevant identified uses of the substance or mixture and uses advised against:**
Relevant uses: Spray paint
Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Details of the supplier of the safety data sheet:**
MONTANA COLORS, S.L.
Pol. Ind. Pla de les Vives C/ Anaïs Nin 6
08295 Sant Vicenç de Castellet - Barcelona - España
Phone.: +34 938332760 (9:00- 16:00h GMT +1:00)
msds@montanacolors.com
<https://www.montanacolors.com>
- 1.4 Emergency telephone number:** +34 938332760 (Mon- frid 9:00- 16:00h GMT +1:00)

SECTION 2: HAZARDS IDENTIFICATION

- 2.1 Classification of the substance or mixture:**
CLP Regulation (EC) No 1272/2008:
Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.
Aerosol 1: Pressurised container: May burst if heated., H229
Aerosol 1: Flammable aerosols, Category 1, H222
Eye Irrit. 2: Eye irritation, Category 2, H319
Skin Irrit. 2: Skin irritation, Category 2, H315
STOT RE 2: Specific target organ toxicity, repeated exposure, Category 2, H373
STOT SE 3: Specific toxicity causing drowsiness and dizziness, single exposure, Category 3, H336
STOT SE 3: Respiratory tract toxicity, single exposure, Category 3, H335

2.2 Label elements:

CLP Regulation (EC) No 1272/2008:

Danger



Hazard statements:

Aerosol 1: H229 - Pressurised container: May burst if heated.
Aerosol 1: H222 - Extremely flammable aerosol.
Eye Irrit. 2: H319 - Causes serious eye irritation.
Skin Irrit. 2: H315 - Causes skin irritation.
STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure.
STOT SE 3: H336 - May cause drowsiness or dizziness.
STOT SE 3: H335 - May cause respiratory irritation.

Precautionary statements:

P101: If medical advice is needed, have product container or label at hand.
P102: Keep out of reach of children.
P103: Read label before use.
P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211: Do not spray on an open flame or other ignition source.
P251: Do not pierce or burn, even after use.
P260: Do not breathe spray.
P271: Use only outdoors or in a well-ventilated area.
P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F
P501: Dispose of contents/container according to the separated collection system used in your municipality.

Substances that contribute to the classification

Reaction mass of ethylbenzene and m-xylene and p-xylene ; Ethyl acetate

- CONTINUED ON NEXT PAGE -



EX014H0101 - MTN HARDCORE SILVER

SECTION 2: HAZARDS IDENTIFICATION (continued)

UFI: JWA0-50Y7-9009-U01M

2.3 Other hazards:

Product fails to meet PBT/vPvB criteria

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance:

Non-applicable

3.2 Mixture:

Chemical description: Aerosol

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

Identification	Chemical name/Classification		Concentration
CAS: Non-applicable EC: 905-562-9 Index: Non-applicable REACH: 01-2119555267-33-XXXX	Reaction mass of ethylbenzene and m-xylene and p-xylene⁽¹⁾ Self-classified		20 - <30 %
	Regulation 1272/2008	Acute Tox. 4: H312+H332; Asp. Tox. 1: H304; Eye Irrit. 2: H319; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT RE 2: H373; STOT SE 3: H335 - Danger	
CAS: 141-78-6 EC: 205-500-4 Index: 607-022-00-5 REACH: 01-2119475103-46-XXXX	Ethyl acetate⁽¹⁾ ATP CLP00		20 - <30 %
	Regulation 1272/2008	Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336; EUH066 - Danger	
CAS: 106-97-8 EC: 203-448-7 Index: 601-004-00-0 REACH: 01-2119474691-32-XXXX	Butane⁽²⁾ ATP CLP00		10 - <20 %
	Regulation 1272/2008	Flam. Gas 1A: H220; Press. Gas: H280 - Danger	
CAS: 74-98-6 EC: 200-827-9 Index: 601-003-00-5 REACH: 01-2119486944-21-XXXX	Propane⁽²⁾ ATP CLP00		5 - <10 %
	Regulation 1272/2008	Flam. Gas 1A: H220; Press. Gas: H280 - Danger	
CAS: 75-28-5 EC: 200-857-2 Index: 601-004-00-0 REACH: 01-2119485395-27-XXXX	Isobutane⁽²⁾ ATP CLP00		5 - <10 %
	Regulation 1272/2008	Flam. Gas 1A: H220; Press. Gas: H280 - Danger	
CAS: Non-applicable EC: 918-481-9 Index: Non-applicable REACH: 01-2119457273-39-XXXX	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics⁽¹⁾ Self-classified		1 - <2,5 %
	Regulation 1272/2008	Asp. Tox. 1: H304; EUH066 - Danger	

⁽¹⁾ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2015/830

⁽²⁾ Voluntarily-listed substance failing to meet any of the criteria set out in Regulation (EU) No. 2015/830

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

- CONTINUED ON NEXT PAGE -



SECTION 4: FIRST AID MEASURES (continued)

By eye contact:

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case removal could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS for the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media:

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO₂).

Unsuitable extinguishing media:

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Destroy any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

6.2 Environmental precautions:

This product is not classified as hazardous to the environment. Keep product away from drains, surface and ground water.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

- CONTINUED ON NEXT PAGE -



SECTION 7: HANDLING AND STORAGE (continued)

7.1 Precautions for safe handling:

A.- Precautions for safe manipulation

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Avoid the evaporation of the product as it contains flammable substances, which could form flammable vapour/air mixtures in the presence of sources of ignition. Control sources of ignition (mobile phones, sparks,...) and transfer at slow speeds to avoid the creation of electrostatic charges. Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations to prevent ergonomic and toxicological risks

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.: 5 °C
 Maximum Temp.: 30 °C
 Maximum time: 120 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

Identification	Occupational exposure limits		
	IOELV (8h)	200 ppm	734 mg/m ³
Ethyl acetate CAS: 141-78-6 EC: 205-500-4	IOELV (STEL)	400 ppm	1468 mg/m ³

DNEL (Workers):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Non-applicable EC: 905-562-9	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	212 mg/kg	Non-applicable
	Inhalation	442 mg/m ³	442 mg/m ³	221 mg/m ³	221 mg/m ³
Ethyl acetate CAS: 141-78-6 EC: 205-500-4	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	63 mg/kg	Non-applicable
	Inhalation	1468 mg/m ³	1468 mg/m ³	734 mg/m ³	734 mg/m ³

DNEL (General population):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Non-applicable EC: 905-562-9	Oral	Non-applicable	Non-applicable	12,5 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	125 mg/kg	Non-applicable
	Inhalation	260 mg/m ³	260 mg/m ³	65,3 mg/m ³	65,3 mg/m ³

- CONTINUED ON NEXT PAGE -



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Ethyl acetate CAS: 141-78-6 EC: 205-500-4	Oral	Non-applicable	Non-applicable	4,5 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	37 mg/kg	Non-applicable
	Inhalation	734 mg/m ³	734 mg/m ³	367 mg/m ³	367 mg/m ³

PNEC:

Identification		Short exposure		Long exposure	
Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Non-applicable EC: 905-562-9	STP	6,58 mg/L	Fresh water	0,327 mg/L	
	Soil	2,31 mg/kg	Marine water	0,327 mg/L	
	Intermittent	0,327 mg/L	Sediment (Fresh water)	12,46 mg/kg	
	Oral	Non-applicable	Sediment (Marine water)	12,46 mg/kg	
Ethyl acetate CAS: 141-78-6 EC: 205-500-4	STP	650 mg/L	Fresh water	0,24 mg/L	
	Soil	0,148 mg/kg	Marine water	0,024 mg/L	
	Intermittent	1,65 mg/L	Sediment (Fresh water)	1,15 mg/kg	
	Oral	0,2 g/kg	Sediment (Marine water)	0,115 mg/kg	



8.2 Exposure controls:

A.- General security and hygiene measures in the work place



In accordance with the order of importance to control professional exposure (Directive 98/24/EC) it is recommended to use localized extraction in the work area as a collective protection measure to avoid exceeding the occupational exposure limits. In case of using personal protective equipment it should have CE marking in accordance with Directive 2016/425/EC. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For additional information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection



Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory respiratory tract protection	Filter mask for gases, vapours and particles		EN 149:2001+A1:2009 EN 405:2002+A1:2010	Replace when an increase in resistance to breathing is observed and/or a smell or taste of the contaminant is detected.

C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory hand protection	NON-disposable chemical protective gloves		EN ISO 374-1:2016+A1:2018 EN 16523-1:2015+A1:2018 EN 420:2004+A1:2010	The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used. Do not use protective creams after the product has come into contact with skin.

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Ocular and facial protection





Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory face protection	Face shield		EN 166:2002 EN 167:2002 EN 168:2002 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection



- CONTINUED ON NEXT PAGE -



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory complete body protection	Disposable clothing for protection against chemical risks, with antistatic and fireproof properties		EN 1149-1,2,3 EN 13034:2005+A1:2009 EN ISO 13982-1:2004/A1:2010 EN ISO 6529:2013 EN ISO 6530:2005 EN ISO 13688:2013 EN 464:1994	For professional use only. Clean periodically according to the manufacturer's instructions.
 Mandatory foot protection	Safety footwear for protection against chemical risk, with antistatic and heat resistant properties		EN ISO 13287:2013 EN ISO 20345:2011 EN 13832-1:2019	Replace boots at any sign of deterioration.

F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	 Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply):	82,35 % weight
V.O.C. density at 20 °C:	624,18 kg/m ³ (624,18 g/L)
Average carbon number:	6,4
Average molecular weight:	99,25 g/mol

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 °C:	Aerosol
Appearance:	Not available
Colour:	According to the markings on the package
Odour:	Not available
Odour threshold:	Non-applicable *

Volatility:

Boiling point at atmospheric pressure:	-1 °C (Propellant)
Vapour pressure at 20 °C:	Non-applicable *
Vapour pressure at 50 °C:	<300000 Pa (300 kPa)
Evaporation rate at 20 °C:	Non-applicable *

Product description:

Density at 20 °C:	758 kg/m ³
Relative density at 20 °C:	Non-applicable *
Dynamic viscosity at 20 °C:	Non-applicable *
Kinematic viscosity at 20 °C:	Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -



SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Kinematic viscosity at 40 °C:	Non-applicable *
Concentration:	Non-applicable *
pH:	Non-applicable *
Vapour density at 20 °C:	Non-applicable *
Partition coefficient n-octanol/water 20 °C:	Non-applicable *
Solubility in water at 20 °C:	
Solubility properties:	Non-applicable *
Decomposition temperature:	Non-applicable *
Melting point/freezing point:	Non-applicable *
Recipient pressure:	Non-applicable *
Explosive properties:	Non-applicable *
Oxidising properties:	Non-applicable *
Flammability:	
Flash Point:	-60 °C (Propellant)
Heat of combustion:	Non-applicable *
Flammability (solid, gas):	Non-applicable *
Autoignition temperature:	365 °C (Propellant)
Lower flammability limit:	Non-applicable *
Upper flammability limit:	Non-applicable *
Explosive:	
Lower explosive limit:	Non-applicable *
Upper explosive limit:	Non-applicable *
9.2 Other information:	
Surface tension at 20 °C:	Non-applicable *
Refraction index:	Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases. Can react violently

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

- CONTINUED ON NEXT PAGE -



SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.

B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Produces skin inflammation.
- Contact with the eyes: Produces eye damage after contact.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for the effects mentioned. For more information see section 3.
IARC: Reaction mass of ethylbenzene and m-xylene and p-xylene (3); Hydrocarbons, C9, aromatics (3)
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensitising effects. For more information see section 3.
- Cutaneous: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

F- Specific target organ toxicity (STOT) - single exposure:

Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.
- Skin: Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.

H- Aspiration hazard:

Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.

Other information:

Non-applicable

Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
	LD50 oral	LD50 dermal	
Butane	>2000 mg/kg	>2000 mg/kg	
CAS: 106-97-8			
EC: 203-448-7	LC50 inhalation	658 mg/L (4 h)	Rat



SECTION 11: TOXICOLOGICAL INFORMATION (continued)

Identification	Acute toxicity		Genus
	LD50 oral	LD50 dermal	
Propane CAS: 74-98-6 EC: 200-827-9	LD50 oral	>2000 mg/kg	
	LD50 dermal	>2000 mg/kg	
	LC50 inhalation	>5 mg/L (4 h)	
Isobutane CAS: 75-28-5 EC: 200-857-2	LD50 oral	>2000 mg/kg	
	LD50 dermal	>2000 mg/kg	
	LC50 inhalation	>5 mg/L (4 h)	
Ethyl acetate CAS: 141-78-6 EC: 205-500-4	LD50 oral	4100 mg/kg	Rat
	LD50 dermal	20000 mg/kg	Rabbit
	LC50 inhalation	>20 mg/L (4 h)	
Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Non-applicable EC: 905-562-9	LD50 oral	5627 mg/kg	Mouse
	LD50 dermal	1100 mg/kg	Rat
	LC50 inhalation	11 mg/L (4 h) (ATEI)	
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics CAS: Non-applicable EC: 918-481-9	LD50 oral	>2000 mg/kg	
	LD50 dermal	>2000 mg/kg	
	LC50 inhalation	>20 mg/L (4 h)	

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

Identification	Acute toxicity		Species	Genus
	LC50	EC50		
Ethyl acetate CAS: 141-78-6 EC: 205-500-4	LC50	230 mg/L (96 h)	Pimephales promelas	Fish
	EC50	717 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	3300 mg/L (48 h)	Scenedesmus subspicatus	Algae

12.2 Persistence and degradability:

Identification	Degradability		Biodegradability	
	BOD5	COD	Concentration	Period
Ethyl acetate CAS: 141-78-6 EC: 205-500-4	BOD5	1,36 g O2/g	Concentration	100 mg/L
	COD	1,69 g O2/g	Period	14 days
	BOD5/COD	0,8	% Biodegradable	83 %

12.3 Bioaccumulative potential:

Identification	Bioaccumulation potential	
	BCF	Pow Log
Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Non-applicable EC: 905-562-9	BCF	9
	Pow Log	2.77
	Potential	Low
Ethyl acetate CAS: 141-78-6 EC: 205-500-4	BCF	30
	Pow Log	0.73
	Potential	Moderate
Butane CAS: 106-97-8 EC: 203-448-7	BCF	33
	Pow Log	2.89
	Potential	Moderate
Propane CAS: 74-98-6 EC: 200-827-9	BCF	13
	Pow Log	2.86
	Potential	Low
Isobutane CAS: 75-28-5 EC: 200-857-2	BCF	27
	Pow Log	2.76
	Potential	Low

12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
	Koc	Conclusion	Henry	Dry soil
	Ethyl acetate CAS: 141-78-6 EC: 205-500-4	59	Very High	13,58 Pa·m ³ /mol
	Surface tension	2,324E-2 N/m (25 °C)	Moist soil	Yes

- CONTINUED ON NEXT PAGE -



SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Absorption/desorption		Volatility	
Butane CAS: 106-97-8 EC: 203-448-7	Koc	900	Henry	96258,75 Pa·m ³ /mol
	Conclusion	Low	Dry soil	Yes
	Surface tension	1,187E-2 N/m (25 °C)	Moist soil	Yes
Propane CAS: 74-98-6 EC: 200-827-9	Koc	460	Henry	71636,78 Pa·m ³ /mol
	Conclusion	Moderate	Dry soil	Yes
	Surface tension	7,02E-3 N/m (25 °C)	Moist soil	Yes
Isobutane CAS: 75-28-5 EC: 200-857-2	Koc	35	Henry	120576,75 Pa·m ³ /mol
	Conclusion	Very High	Dry soil	Yes
	Surface tension	9,84E-3 N/m (25 °C)	Moist soil	Yes

12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

12.6 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
16 05 04*	gases in pressure containers (including halons) containing hazardous substances	Dangerous

Type of waste (Regulation (EU) No 1357/2014):

HP3 Flammable, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP6 Acute Toxicity, HP4 Irritant — skin irritation and eye damage

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommend disposal down the drain. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2021 and RID 2021:



- 14.1 UN number:** UN1950
- 14.2 UN proper shipping name:** AEROSOLS, flammable
- 14.3 Transport hazard class(es):** 2
- Labels: 2.1
- 14.4 Packing group:** N/A
- 14.5 Environmental hazards:** No
- 14.6 Special precautions for user**
 - Special regulations: 190, 327, 344, 625
 - Tunnel restriction code: D
 - Physico-Chemical properties: see section 9
 - Limited quantities: 1 L
- 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:** Non-applicable

Transport of dangerous goods by sea:

- CONTINUED ON NEXT PAGE -



SECTION 14: TRANSPORT INFORMATION (continued)

With regard to IMDG 39-18:



- 14.1 UN number:** UN1950
- 14.2 UN proper shipping name:** AEROSOLS, flammable
- 14.3 Transport hazard class(es):** 2
Labels: 2.1
- 14.4 Packing group:** N/A
- 14.5 Marine pollutant:** No
- 14.6 Special precautions for user**
Special regulations: 63, 959, 190, 277, 327, 344
EmS Codes: F-D, S-U
Physico-Chemical properties: see section 9
Limited quantities: 1 L
Segregation group: Non-applicable
- 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:** Non-applicable

Transport of dangerous goods by air:

With regard to IATA/ICAO 2021:



- 14.1 UN number:** UN1950
- 14.2 UN proper shipping name:** AEROSOLS, flammable
- 14.3 Transport hazard class(es):** 2
Labels: 2.1
- 14.4 Packing group:** N/A
- 14.5 Environmental hazards:** No
- 14.6 Special precautions for user**
Physico-Chemical properties: see section 9
- 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:** Non-applicable

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable
Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable
Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable
Article 95, REGULATION (EU) No 528/2012: Non-applicable
REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Seveso III:

Section	Description	Lower-tier requirements	Upper-tier requirements
P3a	FLAMMABLE AEROSOLS	150	500

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Shall not be used in:
—ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
—tricks and jokes,
—games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

- CONTINUED ON NEXT PAGE -



SECTION 15: REGULATORY INFORMATION (continued)

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (Regulation (EC) No 2015/830).

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

Non-applicable

Texts of the legislative phrases mentioned in section 2:

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

H335: May cause respiratory irritation.

H315: Causes skin irritation.

H373: May cause damage to organs through prolonged or repeated exposure.

H229: Pressurised container: May burst if heated.

H222: Extremely flammable aerosol.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

Acute Tox. 4: H312+H332 - Harmful in contact with skin or if inhaled.

Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.

Eye Irrit. 2: H319 - Causes serious eye irritation.

Flam. Gas 1A: H220 - Extremely flammable gas.

Flam. Liq. 2: H225 - Highly flammable liquid and vapour.

Flam. Liq. 3: H226 - Flammable liquid and vapour.

Press. Gas: H280 - Contains gas under pressure, may explode if heated.

Skin Irrit. 2: H315 - Causes skin irritation.

STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure.

STOT SE 3: H335 - May cause respiratory irritation.

STOT SE 3: H336 - May cause drowsiness or dizziness.

Classification procedure:

Eye Irrit. 2: Calculation method

STOT SE 3: Calculation method

STOT SE 3: Calculation method

Skin Irrit. 2: Calculation method

STOT RE 2: Calculation method

Aerosol 1: Calculation method

Aerosol 1: Calculation method

Advice related to training:

Minimal training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

<http://echa.europa.eu>

<http://eur-lex.europa.eu>

Abbreviations and acronyms:



SECTION 16: OTHER INFORMATION (continued)

ADR: European agreement concerning the international carriage of dangerous goods by road
IMDG: International maritime dangerous goods code
IATA: International Air Transport Association
ICAO: International Civil Aviation Organisation
COD: Chemical Oxygen Demand
BOD5: 5-day biochemical oxygen demand
BCF: Bioconcentration factor
LD50: Lethal Dose 50
LC50: Lethal Concentration 50
EC50: Effective concentration 50
Log-POW: Octanol-water partition coefficient
Koc: Partition coefficient of organic carbon

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -