




SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

- 1.1 Product identifier:** EX0179010 - MTN MAXIMO White
Other means of identification:
UFI: VK21-T061-400X-F3VN
- 1.2 Relevant identified uses of the substance or mixture and uses advised against:**
Relevant uses: Spray paint
Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Details of the supplier of the safety data sheet:**
MONTANA COLORS, S.L.
Pol. Ind. Pla de les Vives C/ Anaïs Nin 6
08295 Sant Vicenç de Castellet - Barcelona - España
Phone: +34 938332760 (9:00- 16:00h GMT +1:00)
msds@montanacolors.com
<https://www.montanacolors.com>
- 1.4 Emergency telephone number:** +34 938332760 (Mon- frid 9:00- 16:00h GMT +1:00)

SECTION 2: HAZARDS IDENTIFICATION **

- 2.1 Classification of the substance or mixture:**
CLP Regulation (EC) No 1272/2008:
Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.
Aerosol 1: Pressurised container: May burst if heated., H229
Aerosol 1: Flammable aerosols, Category 1, H222
Eye Irrit. 2: Eye irritation, Category 2, H319
Skin Sens. 1A: Sensitisation, skin, Category 1A, H317
STOT SE 3: Specific toxicity causing drowsiness and dizziness, single exposure, Category 3, H336
- 2.2 Label elements:**
CLP Regulation (EC) No 1272/2008:
Danger
- 
- Hazard statements:**
Aerosol 1: H229 - Pressurised container: May burst if heated.
Aerosol 1: H222 - Extremely flammable aerosol.
Eye Irrit. 2: H319 - Causes serious eye irritation.
Skin Sens. 1A: H317 - May cause an allergic skin reaction.
STOT SE 3: H336 - May cause drowsiness or dizziness.
- Precautionary statements:**
P101: If medical advice is needed, have product container or label at hand.
P102: Keep out of reach of children.
P103: Read label before use.
P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211: Do not spray on an open flame or other ignition source.
P251: Do not pierce or burn, even after use.
P261: Avoid breathing spray.
P271: Use only outdoors or in a well-ventilated area.
P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F
P501: Dispose of contents/container according to the separated collection system used in your municipality.
- Supplementary information:**
EUH066: Repeated exposure may cause skin dryness or cracking.
Contains maleic anhydride, Reaction mass of: N,N-Ethane-1,2-diylbis(decanamide)/12-Hydroxy-N-[2-[1-oxydecyl]amino]ethyl] octadecanamide/N,N-Ethane-1,2-diylbis(12-hydroxyoctadecanamide).
EUH211: Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

** Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -



SECTION 2: HAZARDS IDENTIFICATION ** (continued)

Substances that contribute to the classification

Ethyl acetate; N-butyl acetate; Cobalt bis(2-ethylhexanoate)

UFI: VK21-T061-400X-F3VN

2.3 Other hazards:

Product fails to meet PBT/vPvB criteria

** Changes with regards to the previous version

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS **

3.1 Substance:

Non-applicable

3.2 Mixture:

Chemical description: Aerosol

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

| Identification | Chemical name/Classification | | Concentration |
|---|--|---|---------------|
| CAS: 141-78-6 EC: 205-500-4 Index: 607-022-00-5 REACH: 01-2119475103-46-XXXX | Ethyl acetate⁽¹⁾ ATP CLP00 | | 20 - <30 % |
| | Regulation 1272/2008 | Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336; EUH066 - Danger | |
| CAS: 123-86-4 EC: 204-658-1 Index: 607-025-00-1 REACH: 01-2119485493-29-XXXX | N-butyl acetate⁽¹⁾ ATP CLP00 | | 10 - <20 % |
| | Regulation 1272/2008 | Flam. Liq. 3: H226; STOT SE 3: H336; EUH066 - Warning | |
| CAS: 106-97-8 EC: 203-448-7 Index: 601-004-00-0 REACH: 01-2119474691-32-XXXX | Butane⁽²⁾ ATP CLP00 | | 5 - <10 % |
| | Regulation 1272/2008 | Flam. Gas 1A: H220; Press. Gas: H280 - Danger | |
| CAS: 74-98-6 EC: 200-827-9 Index: 601-003-00-5 REACH: 01-2119486944-21-XXXX | Propane⁽²⁾ ATP CLP00 | | 5 - <10 % |
| | Regulation 1272/2008 | Flam. Gas 1A: H220; Press. Gas: H280 - Danger | |
| CAS: 75-28-5 EC: 200-857-2 Index: 601-004-00-0 REACH: 01-2119485395-27-XXXX | Isobutane⁽²⁾ ATP CLP00 | | 2,5 - <5 % |
| | Regulation 1272/2008 | Flam. Gas 1A: H220; Press. Gas: H280 - Danger | |
| CAS: Non-applicable EC: 905-562-9 Index: Non-applicable REACH: 01-2119555267-33-XXXX | Reaction mass of ethylbenzene and m-xylene and p-xylene⁽¹⁾ Self-classified | | 2,5 - <5 % |
| | Regulation 1272/2008 | Acute Tox. 4: H312+H332; Asp. Tox. 1: H304; Eye Irrit. 2: H319; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT RE 2: H373; STOT SE 3: H335 - Danger | |
| CAS: 108-65-6 EC: 203-603-9 Index: 607-195-00-7 REACH: 01-2119475791-29-XXXX | 2-methoxy-1-methylethyl acetate⁽³⁾ Self-classified | | 0,3 - <1 % |
| | Regulation 1272/2008 | Flam. Liq. 3: H226; STOT SE 3: H336 - Warning | |
| CAS: 1330-20-7 EC: 215-535-7 Index: 601-022-00-9 REACH: 01-2119488216-32-XXXX | Xylene⁽³⁾ Self-classified | | 0,05 - <0,3 % |
| | Regulation 1272/2008 | Acute Tox. 4: H312+H332; Aquatic Chronic 3: H412; Asp. Tox. 1: H304; Eye Irrit. 2: H319; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT RE 2: H373; STOT SE 3: H335 - Danger | |
| CAS: 22464-99-9 EC: 245-018-1 Index: Non-applicable REACH: 01-2119979088-21-XXXX | 2-ethylhexanoic acid, zirconium salt⁽¹⁾ Self-classified | | 0,05 - <0,3 % |
| | Regulation 1272/2008 | Repr. 2: H361d - Warning | |

⁽¹⁾ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2015/830

⁽²⁾ Voluntarily-listed substance failing to meet any of the criteria set out in Regulation (EU) No. 2015/830

⁽³⁾ Substance with a Union workplace exposure limit

** Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -



SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS ** (continued)

| Identification | Chemical name/Classification | | Concentration |
|---|---|-----------------|---------------|
| CAS: Non-applicable EC: 430-050-2 Index: 616-127-00-5 REACH: 01-2120789217-43-XXXX | Reaction mass of: N,N-Ethane-1,2-diylbis(decanamide)/12-Hydroxy-N-[2-[1-oxydecyl)amino]ethyl]octadecanamide/N,N-Ethane-1,2-diylbis(12-hydroxyoctadecanamide)⁽¹⁾ | ATP CLP00 | 0,05 - <0,3 % |
| Regulation 1272/2008 | Aquatic Chronic 2: H411; Skin Sens. 1: H317 - Warning | | |
| CAS: 136-52-7 EC: 205-250-6 Index: Non-applicable REACH: 01-2119524678-29-XXXX | Cobalt bis(2-ethylhexanoate)⁽¹⁾ | Self-classified | 0,05 - <0,3 % |
| Regulation 1272/2008 | Aquatic Acute 1: H400; Aquatic Chronic 3: H412; Eye Irrit. 2: H319; Repr. 1B: H360; Skin Sens. 1A: H317 - Danger | | |
| CAS: 100-41-4 EC: 202-849-4 Index: 601-023-00-4 REACH: 01-2119489370-35-XXXX | Ethylbenzene⁽³⁾ | ATP ATP06 | 0,05 - <0,3 % |
| Regulation 1272/2008 | Acute Tox. 4: H332; Asp. Tox. 1: H304; Flam. Liq. 2: H225; STOT RE 2: H373 - Danger | | |
| CAS: 108-31-6 EC: 203-571-6 Index: 607-096-00-9 REACH: 01-2119472428-31-XXXX | maleic anhydride⁽¹⁾ | ATP ATP13 | <0,05 % |
| Regulation 1272/2008 | Acute Tox. 4: H302; Eye Dam. 1: H318; Resp. Sens. 1: H334; Skin Corr. 1B: H314; Skin Sens. 1A: H317; STOT RE 1: H372; EUH071 - Danger | | |

⁽¹⁾ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2015/830

⁽²⁾ Voluntarily-listed substance failing to meet any of the criteria set out in Regulation (EU) No. 2015/830

⁽³⁾ Substance with a Union workplace exposure limit

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

** Changes with regards to the previous version

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media:

- CONTINUED ON NEXT PAGE -



SECTION 5: FIREFIGHTING MEASURES (continued)

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO₂).

Unsuitable extinguishing media:

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Destroy any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

For emergency responders:

See section 8.

6.2 Environmental precautions:

Avoid spillage into the aquatic environment as it contains substances potentially dangerous for this. Contain the product absorbed in hermetically sealed containers. In the case of serious spillage into the aquatic environment notify the relevant authority.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- Precautions for safe manipulation

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Avoid the evaporation of the product as it contains flammable substances, which could form flammable vapour/air mixtures in the presence of sources of ignition. Control sources of ignition (mobile phones, sparks,...) and transfer at slow speeds to avoid the creation of electrostatic charges. Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations to prevent ergonomic and toxicological risks

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

- CONTINUED ON NEXT PAGE -



SECTION 7: HANDLING AND STORAGE (continued)

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

| | |
|----------------|------------|
| Minimum Temp.: | 5 °C |
| Maximum Temp.: | 30 °C |
| Maximum time: | 120 Months |

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

| Identification | Occupational exposure limits | | |
|--|------------------------------|---------|------------------------|
| | IOELV (8h) | 50 ppm | 241 mg/m ³ |
| N-butyl acetate CAS: 123-86-4 EC: 204-658-1 | IOELV (STEL) | 150 ppm | 723 mg/m ³ |
| Ethylbenzene CAS: 100-41-4 EC: 202-849-4 | IOELV (8h) | 100 ppm | 442 mg/m ³ |
| | IOELV (STEL) | 200 ppm | 884 mg/m ³ |
| Xylene CAS: 1330-20-7 EC: 215-535-7 | IOELV (8h) | 50 ppm | 221 mg/m ³ |
| | IOELV (STEL) | 100 ppm | 442 mg/m ³ |
| 2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9 | IOELV (8h) | 50 ppm | 275 mg/m ³ |
| | IOELV (STEL) | 100 ppm | 550 mg/m ³ |
| Ethyl acetate CAS: 141-78-6 EC: 205-500-4 | IOELV (8h) | 200 ppm | 734 mg/m ³ |
| | IOELV (STEL) | 400 ppm | 1468 mg/m ³ |

DNEL (Workers):

| Identification | | Short exposure | | Long exposure | |
|---|------------|------------------------|------------------------|-------------------------|-----------------------|
| | | Systemic | Local | Systemic | Local |
| Ethyl acetate CAS: 141-78-6 EC: 205-500-4 | Oral | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| | Dermal | Non-applicable | Non-applicable | 63 mg/kg | Non-applicable |
| | Inhalation | 1468 mg/m ³ | 1468 mg/m ³ | 734 mg/m ³ | 734 mg/m ³ |
| N-butyl acetate CAS: 123-86-4 EC: 204-658-1 | Oral | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| | Dermal | 11 mg/kg | Non-applicable | 11 mg/kg | Non-applicable |
| | Inhalation | 600 mg/m ³ | 600 mg/m ³ | 300 mg/m ³ | 300 mg/m ³ |
| Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Non-applicable EC: 905-562-9 | Oral | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| | Dermal | Non-applicable | Non-applicable | 212 mg/kg | Non-applicable |
| | Inhalation | 442 mg/m ³ | 442 mg/m ³ | 221 mg/m ³ | 221 mg/m ³ |
| 2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9 | Oral | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| | Dermal | Non-applicable | Non-applicable | 796 mg/kg | Non-applicable |
| | Inhalation | Non-applicable | 550 mg/m ³ | 275 mg/m ³ | Non-applicable |
| Xylene CAS: 1330-20-7 EC: 215-535-7 | Oral | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| | Dermal | Non-applicable | Non-applicable | 212 mg/kg | Non-applicable |
| | Inhalation | 442 mg/m ³ | 442 mg/m ³ | 221 mg/m ³ | 221 mg/m ³ |
| 2-ethylhexanoic acid, zirconium salt CAS: 22464-99-9 EC: 245-018-1 | Oral | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| | Dermal | Non-applicable | Non-applicable | 6,49 mg/kg | Non-applicable |
| | Inhalation | Non-applicable | Non-applicable | 32,97 mg/m ³ | Non-applicable |

- CONTINUED ON NEXT PAGE -



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

| Identification | | Short exposure | | Long exposure | |
|--|------------|-----------------------|-----------------------|-------------------------|--------------------------|
| | | Systemic | Local | Systemic | Local |
| Reaction mass of: N,N-Ethane-1,2-diylbis(decanamide)/12-Hydroxy-N-[2-[1-oxydecyl]amino]ethyl]octadecanamide/N,N-Ethane-1,2-diylbis(12-hydroxyoctadecanamide) CAS: Non-applicable EC: 430-050-2 | Oral | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| | Dermal | Non-applicable | Non-applicable | 5 mg/kg | Non-applicable |
| | Inhalation | Non-applicable | Non-applicable | 17,62 mg/m ³ | Non-applicable |
| Cobalt bis(2-ethylhexanoate) CAS: 136-52-7 EC: 205-250-6 | Oral | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| | Dermal | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| | Inhalation | Non-applicable | Non-applicable | Non-applicable | 0,2351 mg/m ³ |
| Ethylbenzene CAS: 100-41-4 EC: 202-849-4 | Oral | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| | Dermal | Non-applicable | Non-applicable | 180 mg/kg | Non-applicable |
| | Inhalation | Non-applicable | 293 mg/m ³ | 77 mg/m ³ | Non-applicable |
| maleic anhydride CAS: 108-31-6 EC: 203-571-6 | Oral | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| | Dermal | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| | Inhalation | 0,2 mg/m ³ | 0,2 mg/m ³ | 0,081 mg/m ³ | 0,081 mg/m ³ |

DNEL (General population):

| Identification | | Short exposure | | Long exposure | |
|--|------------|-----------------------|-----------------------|------------------------|-------------------------|
| | | Systemic | Local | Systemic | Local |
| Ethyl acetate CAS: 141-78-6 EC: 205-500-4 | Oral | Non-applicable | Non-applicable | 4,5 mg/kg | Non-applicable |
| | Dermal | Non-applicable | Non-applicable | 37 mg/kg | Non-applicable |
| | Inhalation | 734 mg/m ³ | 734 mg/m ³ | 367 mg/m ³ | 367 mg/m ³ |
| N-butyl acetate CAS: 123-86-4 EC: 204-658-1 | Oral | 2 mg/kg | Non-applicable | 2 mg/kg | Non-applicable |
| | Dermal | 6 mg/kg | Non-applicable | 6 mg/kg | Non-applicable |
| | Inhalation | 300 mg/m ³ | 300 mg/m ³ | 35,7 mg/m ³ | 35,7 mg/m ³ |
| Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Non-applicable EC: 905-562-9 | Oral | Non-applicable | Non-applicable | 12,5 mg/kg | Non-applicable |
| | Dermal | Non-applicable | Non-applicable | 125 mg/kg | Non-applicable |
| | Inhalation | 260 mg/m ³ | 260 mg/m ³ | 65,3 mg/m ³ | 65,3 mg/m ³ |
| 2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9 | Oral | Non-applicable | Non-applicable | 36 mg/kg | Non-applicable |
| | Dermal | Non-applicable | Non-applicable | 320 mg/kg | Non-applicable |
| | Inhalation | Non-applicable | Non-applicable | 33 mg/m ³ | 33 mg/m ³ |
| Xylene CAS: 1330-20-7 EC: 215-535-7 | Oral | Non-applicable | Non-applicable | 12,5 mg/kg | Non-applicable |
| | Dermal | Non-applicable | Non-applicable | 125 mg/kg | Non-applicable |
| | Inhalation | 260 mg/m ³ | 260 mg/m ³ | 65,3 mg/m ³ | 65,3 mg/m ³ |
| 2-ethylhexanoic acid, zirconium salt CAS: 22464-99-9 EC: 245-018-1 | Oral | Non-applicable | Non-applicable | 4,51 mg/kg | Non-applicable |
| | Dermal | Non-applicable | Non-applicable | 3,25 mg/kg | Non-applicable |
| | Inhalation | Non-applicable | Non-applicable | 8,13 mg/m ³ | Non-applicable |
| Reaction mass of: N,N-Ethane-1,2-diylbis(decanamide)/12-Hydroxy-N-[2-[1-oxydecyl]amino]ethyl]octadecanamide/N,N-Ethane-1,2-diylbis(12-hydroxyoctadecanamide) CAS: Non-applicable EC: 430-050-2 | Oral | Non-applicable | Non-applicable | 2,5 mg/kg | Non-applicable |
| | Dermal | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| | Inhalation | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| Cobalt bis(2-ethylhexanoate) CAS: 136-52-7 EC: 205-250-6 | Oral | Non-applicable | Non-applicable | 0,175 mg/kg | Non-applicable |
| | Dermal | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| | Inhalation | Non-applicable | Non-applicable | Non-applicable | 0,037 mg/m ³ |
| Ethylbenzene CAS: 100-41-4 EC: 202-849-4 | Oral | Non-applicable | Non-applicable | 1,6 mg/kg | Non-applicable |
| | Dermal | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| | Inhalation | Non-applicable | Non-applicable | 15 mg/m ³ | Non-applicable |

PNEC:

- CONTINUED ON NEXT PAGE -



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)



| Identification | | | | |
|--|--------------|----------------|-------------------------|---------------|
| Ethyl acetate CAS: 141-78-6 EC: 205-500-4 | STP | 650 mg/L | Fresh water | 0,24 mg/L |
| | Soil | 0,148 mg/kg | Marine water | 0,024 mg/L |
| | Intermittent | 1,65 mg/L | Sediment (Fresh water) | 1,15 mg/kg |
| | Oral | 0,2 g/kg | Sediment (Marine water) | 0,115 mg/kg |
| N-butyl acetate CAS: 123-86-4 EC: 204-658-1 | STP | 35,6 mg/L | Fresh water | 0,18 mg/L |
| | Soil | 0,09 mg/kg | Marine water | 0,018 mg/L |
| | Intermittent | 0,36 mg/L | Sediment (Fresh water) | 0,981 mg/kg |
| | Oral | Non-applicable | Sediment (Marine water) | 0,098 mg/kg |
| Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Non-applicable EC: 905-562-9 | STP | 6,58 mg/L | Fresh water | 0,327 mg/L |
| | Soil | 2,31 mg/kg | Marine water | 0,327 mg/L |
| | Intermittent | 0,327 mg/L | Sediment (Fresh water) | 12,46 mg/kg |
| | Oral | Non-applicable | Sediment (Marine water) | 12,46 mg/kg |
| 2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9 | STP | 100 mg/L | Fresh water | 0,635 mg/L |
| | Soil | 0,29 mg/kg | Marine water | 0,064 mg/L |
| | Intermittent | 6,35 mg/L | Sediment (Fresh water) | 3,29 mg/kg |
| | Oral | Non-applicable | Sediment (Marine water) | 0,329 mg/kg |
| Xylene CAS: 1330-20-7 EC: 215-535-7 | STP | 6,58 mg/L | Fresh water | 0,327 mg/L |
| | Soil | 2,31 mg/kg | Marine water | 0,327 mg/L |
| | Intermittent | 0,327 mg/L | Sediment (Fresh water) | 12,46 mg/kg |
| | Oral | Non-applicable | Sediment (Marine water) | 12,46 mg/kg |
| Reaction mass of: N,N-Ethane-1,2-diylbis(decanamide)/12-Hydroxy-N-[2-[1-oxydecyl]amino]ethyl]octadecanamide/N,N-Ethane-1,2-diylbis(12-hydroxyoctadecanamide) CAS: Non-applicable EC: 430-050-2 | STP | 100 mg/L | Fresh water | 0,000058 mg/L |
| | Soil | 1 mg/kg | Marine water | 0,000006 mg/L |
| | Intermittent | 0,000054 mg/L | Sediment (Fresh water) | 1 mg/kg |
| | Oral | 0,0333 g/kg | Sediment (Marine water) | 0,1 mg/kg |
| Cobalt bis(2-ethylhexanoate) CAS: 136-52-7 EC: 205-250-6 | STP | 0,37 mg/L | Fresh water | 0,00062 mg/L |
| | Soil | 10,9 mg/kg | Marine water | 0,00236 mg/L |
| | Intermittent | Non-applicable | Sediment (Fresh water) | 53,8 mg/kg |
| | Oral | Non-applicable | Sediment (Marine water) | 69,8 mg/kg |
| Ethylbenzene CAS: 100-41-4 EC: 202-849-4 | STP | 9,6 mg/L | Fresh water | 0,1 mg/L |
| | Soil | 2,68 mg/kg | Marine water | 0,01 mg/L |
| | Intermittent | 0,1 mg/L | Sediment (Fresh water) | 13,7 mg/kg |
| | Oral | 0,02 g/kg | Sediment (Marine water) | 1,37 mg/kg |
| maleic anhydride CAS: 108-31-6 EC: 203-571-6 | STP | 44,6 mg/L | Fresh water | 0,038 mg/L |
| | Soil | 0,037 mg/kg | Marine water | 0,004 mg/L |
| | Intermittent | 0,379 mg/L | Sediment (Fresh water) | 0,296 mg/kg |
| | Oral | Non-applicable | Sediment (Marine water) | 0,03 mg/kg |

8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection



| Pictogram | PPE | Labelling | CEN Standard | Remarks |
|---|--|---|---|---|
|  Mandatory respiratory tract protection | Filter mask for gases, vapours and particles |  | EN 149:2001+A1:2009 EN 405:2002+A1:2010 EN ISO 136:1998 | Replace when an increase in resistance to breathing is observed and/or a smell or taste of the contaminant is detected. |

C.- Specific protection for the hands

- CONTINUED ON NEXT PAGE -





SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)





| Pictogram | PPE | Labelling | CEN Standard | Remarks |
|--|--|---|---------------------|--|
|  Mandatory hand protection | Chemical protective gloves (Material: Linear low-density polyethylene (LLDPE), Breakthrough time: > 480 min, Thickness: 0.062 mm) |  | EN 420:2004+A1:2010 | Replace the gloves at any sign of deterioration. |

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.



D.- Ocular and facial protection

| Pictogram | PPE | Labelling | CEN Standard | Remarks |
|--|-------------|---|---|---|
|  Mandatory face protection | Face shield |  | EN 166:2002 EN 167:2002 EN 168:2002 EN ISO 4007:2018 | Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing. |

E.- Body protection

| Pictogram | PPE | Labelling | CEN Standard | Remarks |
|---|---|---|---|---|
|  Mandatory complete body protection | Disposable clothing for protection against chemical risks, with antistatic and fireproof properties |  | EN 1149-1,2,3 EN 13034:2005+A1:2009 EN ISO 13982-1:2004/A1:2010 EN ISO 6529:2013 EN ISO 6530:2005 EN ISO 13688:2013 EN 464:1994 | For professional use only. Clean periodically according to the manufacturer's instructions. |
|  Mandatory foot protection | Safety footwear for protection against chemical risk, with antistatic and heat resistant properties |  | EN ISO 13287:2013 EN ISO 20345:2011 EN 13832-1:2019 | Replace boots at any sign of deterioration. |

F.- Additional emergency measures

| Emergency measure | Standards | Emergency measure | Standards |
|---|---|--|--|
|  Emergency shower | ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011 |  Eyewash stations | DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011 |

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

| | |
|---------------------------|---------------------------------------|
| V.O.C. (Supply): | 62,21 % weight |
| V.O.C. density at 20 °C: | 572,98 kg/m ³ (572,98 g/L) |
| Average carbon number: | 5,12 |
| Average molecular weight: | 99,97 g/mol |

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 °C: Aerosol

Appearance: Not available

*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -



SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

| | |
|--|--------------------------------|
| Colour: | <input type="checkbox"/> White |
| Odour: | Not available |
| Odour threshold: | Non-applicable * |
| Volatility: | |
| Boiling point at atmospheric pressure: | -1 °C (Propellant) |
| Vapour pressure at 20 °C: | Non-applicable * |
| Vapour pressure at 50 °C: | <300000 Pa (300 kPa) |
| Evaporation rate at 20 °C: | Non-applicable * |
| Product description: | |
| Density at 20 °C: | 921 kg/m ³ |
| Relative density at 20 °C: | 0,921 |
| Dynamic viscosity at 20 °C: | Non-applicable * |
| Kinematic viscosity at 20 °C: | Non-applicable * |
| Kinematic viscosity at 40 °C: | Non-applicable * |
| Concentration: | Non-applicable * |
| pH: | Non-applicable * |
| Vapour density at 20 °C: | Non-applicable * |
| Partition coefficient n-octanol/water 20 °C: | Non-applicable * |
| Solubility in water at 20 °C: | Non-applicable * |
| Solubility properties: | Non-applicable * |
| Decomposition temperature: | Non-applicable * |
| Melting point/freezing point: | Non-applicable * |
| Recipient pressure: | Non-applicable * |
| Flammability: | |
| Flash Point: | Non-applicable |
| Flammability (solid, gas): | Non-applicable * |
| Autoignition temperature: | 365 °C (Propellant) |
| Lower flammability limit: | Non-applicable * |
| Upper flammability limit: | Non-applicable * |
| Particle characteristics: | |
| Median equivalent diameter: | Non-applicable |

9.2 Other information:

Information with regard to physical hazard classes:

| | |
|--|------------------|
| Explosive properties: | Non-applicable * |
| Oxidising properties: | Non-applicable * |
| Corrosive to metals: | Non-applicable * |
| Heat of combustion: | Non-applicable * |
| Aerosols-total percentage (by mass) of flammable components: | Non-applicable * |

Other safety characteristics:

| | |
|---------------------------|------------------|
| Surface tension at 20 °C: | Non-applicable * |
| Refraction index: | Non-applicable * |

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

- CONTINUED ON NEXT PAGE -



SECTION 10: STABILITY AND REACTIVITY (continued)

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

| Shock and friction | Contact with air | Increase in temperature | Sunlight | Humidity |
|--------------------|------------------|-------------------------|---------------------|----------------|
| Not applicable | Not applicable | Risk of combustion | Avoid direct impact | Not applicable |

10.5 Incompatible materials:

| Acids | Water | Oxidising materials | Combustible materials | Others |
|--------------------|----------------|---------------------|-----------------------|-------------------------------|
| Avoid strong acids | Not applicable | Avoid | Not applicable | Avoid alkalis or strong bases |

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION **

11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.

B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Prolonged inhalation of the product is corrosive to mucous membranes and the upper respiratory tract

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for skin contact. For more information see section 3.
- Contact with the eyes: Produces eye damage after contact.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for the effects mentioned. For more information see section 3.
IARC: Reaction mass of ethylbenzene and m-xylene and p-xylene (3); Benzyl acetate (3); propan-2-ol (3); ethanol (1); Ethylbenzene (2B); Xylene (3); Titanium dioxide (2B); Cobalt bis(2-ethylhexanoate) (2B); Hydrocarbons, C9-C11,n-alkanes, iso-alkanes, cyclics, <2% aromatics (3)
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.

E- Sensitizing effects:

** Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -



SECTION 11: TOXICOLOGICAL INFORMATION ** (continued)

- Respiratory: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with sensitising effects. For more information see section 3.
- Cutaneous: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.

F- Specific target organ toxicity (STOT) - single exposure:

Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for inhalation. For more information see section 3.
- Skin: Repeated exposure may cause skin dryness or cracking

H- Aspiration hazard:

Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.

Other information:

Non-applicable

Specific toxicology information on the substances:

| Identification | Acute toxicity | | Genus |
|---|-----------------|----------------------|--------|
| | LD50 | LC50 | |
| N-butyl acetate CAS: 123-86-4 EC: 204-658-1 | LD50 oral | 12789 mg/kg | Rat |
| | LD50 dermal | 14112 mg/kg | Rabbit |
| | LC50 inhalation | 23,4 mg/L (4 h) | Rat |
| Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Non-applicable EC: 905-562-9 | LD50 oral | 5627 mg/kg | Mouse |
| | LD50 dermal | 1100 mg/kg | Rat |
| | LC50 inhalation | 11 mg/L (4 h) (ATEi) | |
| Ethyl acetate CAS: 141-78-6 EC: 205-500-4 | LD50 oral | 4100 mg/kg | Rat |
| | LD50 dermal | 20000 mg/kg | Rabbit |
| | LC50 inhalation | >20 mg/L (4 h) | |
| Butane CAS: 106-97-8 EC: 203-448-7 | LD50 oral | >2000 mg/kg | |
| | LD50 dermal | >2000 mg/kg | |
| | LC50 inhalation | 658 mg/L (4 h) | Rat |
| Propane CAS: 74-98-6 EC: 200-827-9 | LD50 oral | >2000 mg/kg | |
| | LD50 dermal | >2000 mg/kg | |
| | LC50 inhalation | >5 mg/L (4 h) | |
| Isobutane CAS: 75-28-5 EC: 200-857-2 | LD50 oral | >2000 mg/kg | |
| | LD50 dermal | >2000 mg/kg | |
| | LC50 inhalation | >5 mg/L (4 h) | |
| 2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9 | LD50 oral | 8532 mg/kg | Rat |
| | LD50 dermal | 5100 mg/kg | Rat |
| | LC50 inhalation | 30 mg/L (4 h) | Rat |
| Xylene CAS: 1330-20-7 EC: 215-535-7 | LD50 oral | 2100 mg/kg | Rat |
| | LD50 dermal | 1100 mg/kg | Rat |
| | LC50 inhalation | >20 mg/L | |
| 2-ethylhexanoic acid, zirconium salt CAS: 22464-99-9 EC: 245-018-1 | LD50 oral | 2043 mg/kg | Rat |
| | LD50 dermal | >2000 mg/kg | |
| | LC50 inhalation | >5 mg/L | |
| Reaction mass of: N,N-Ethane-1,2-diylbis(decanamide)/12-Hydroxy-N-[2-[1-oxydecyl] amino]ethyl]octadecanamide/N,N-Ethane-1,2-diylbis(12-hydroxyoctadecanamide) CAS: Non-applicable EC: 430-050-2 | LD50 oral | 5100 mg/kg | Rat |
| | LD50 dermal | >2000 mg/kg | |
| | LC50 inhalation | >5 mg/L | |
| Cobalt bis(2-ethylhexanoate) CAS: 136-52-7 EC: 205-250-6 | LD50 oral | >2000 mg/kg | |
| | LD50 dermal | >2000 mg/kg | |
| | LC50 inhalation | >5 mg/L | |

** Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -



SECTION 11: TOXICOLOGICAL INFORMATION ** (continued)

| Identification | Acute toxicity | | Genus |
|--|----------------|-------------|-------|
| | LD50 oral | LD50 dermal | |
| Ethylbenzene CAS: 100-41-4 EC: 202-849-4 | 3500 mg/kg | 15354 mg/kg | Rat |
| maleic anhydride CAS: 108-31-6 EC: 203-571-6 | >2000 mg/kg | >2000 mg/kg | |
| | >5 mg/L | | |

** Changes with regards to the previous version

SECTION 12: ECOLOGICAL INFORMATION **

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

Acute toxicity:

| Identification | Concentration | | Species | Genus |
|--|------------------|------------------|-------------------------|------------|
| | LC50 | EC50 | | |
| Ethyl acetate CAS: 141-78-6 EC: 205-500-4 | 230 mg/L (96 h) | 717 mg/L (48 h) | Pimephales promelas | Fish |
| | | 3300 mg/L (48 h) | Daphnia magna | Crustacean |
| | | | Scenedesmus subspicatus | Algae |
| N-butyl acetate CAS: 123-86-4 EC: 204-658-1 | Non-applicable | | | |
| | Non-applicable | | | |
| | 675 mg/L (72 h) | | Scenedesmus subspicatus | Algae |
| 2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9 | 161 mg/L (96 h) | 481 mg/L (48 h) | Pimephales promelas | Fish |
| | | | Daphnia sp. | Crustacean |
| | Non-applicable | | | |
| Xylene CAS: 1330-20-7 EC: 215-535-7 | >10 - 100 (96 h) | >10 - 100 (48 h) | | Fish |
| | | >10 - 100 (72 h) | | Crustacean |
| | | | | Algae |
| 2-ethylhexanoic acid, zirconium salt CAS: 22464-99-9 EC: 245-018-1 | 270 mg/L (96 h) | | N/A | Fish |
| | Non-applicable | | | |
| | Non-applicable | | | |
| Reaction mass of: N,N-Ethane-1,2-diylbis(decanamide)/12-Hydroxy-N-[2-[1-oxydecyl]amino]ethyl]octadecanamide/N,N-Ethane-1,2-diylbis(12-hydroxyoctadecanamide) CAS: Non-applicable EC: 430-050-2 | >1 - 10 (96 h) | >1 - 10 (48 h) | | Fish |
| | | >1 - 10 (72 h) | | Crustacean |
| | | | | Algae |

** Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -



SECTION 12: ECOLOGICAL INFORMATION ** (continued)

| Identification | Concentration | | Species | Genus |
|--|---------------|------------------|---------------------|------------|
| Cobalt bis(2-ethylhexanoate) CAS: 136-52-7 EC: 205-250-6 | LC50 | >0.1 - 1 (96 h) | | Fish |
| | EC50 | >0.1 - 1 (48 h) | | Crustacean |
| | EC50 | >0.1 - 1 (72 h) | | Algae |
| Ethylbenzene CAS: 100-41-4 EC: 202-849-4 | LC50 | 42.3 mg/L (96 h) | Pimephales promelas | Fish |
| | EC50 | 75 mg/L (48 h) | Daphnia magna | Crustacean |
| | EC50 | 63 mg/L (3 h) | Chlorella vulgaris | Algae |

Chronic toxicity:

| Identification | Concentration | | Species | Genus |
|--|---------------|----------------|---------------------|------------|
| Ethyl acetate CAS: 141-78-6 EC: 205-500-4 | NOEC | 9.65 mg/L | Pimephales promelas | Fish |
| | NOEC | 2.4 mg/L | Daphnia magna | Crustacean |
| N-butyl acetate CAS: 123-86-4 EC: 204-658-1 | NOEC | Non-applicable | | |
| | NOEC | 23.2 mg/L | Daphnia magna | Crustacean |
| Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Non-applicable EC: 905-562-9 | NOEC | 1.3 mg/L | Oncorhynchus mykiss | Fish |
| | NOEC | 1.17 mg/L | Ceriodaphnia dubia | Crustacean |
| 2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9 | NOEC | 47.5 mg/L | Oryzias latipes | Fish |
| | NOEC | 100 mg/L | Daphnia magna | Crustacean |
| Xylene CAS: 1330-20-7 EC: 215-535-7 | NOEC | 1.3 mg/L | Oncorhynchus mykiss | Fish |
| | NOEC | 1.17 mg/L | Ceriodaphnia dubia | Crustacean |
| 2-ethylhexanoic acid, zirconium salt CAS: 22464-99-9 EC: 245-018-1 | NOEC | Non-applicable | | |
| | NOEC | 25 mg/L | Daphnia magna | Crustacean |
| Cobalt bis(2-ethylhexanoate) CAS: 136-52-7 EC: 205-250-6 | NOEC | 0.21 mg/L | Pimephales promelas | Fish |
| | NOEC | 0.1697 mg/L | Aeolosoma sp. | Crustacean |
| Ethylbenzene CAS: 100-41-4 EC: 202-849-4 | NOEC | Non-applicable | | |
| | NOEC | 0.96 mg/L | Ceriodaphnia dubia | Crustacean |

12.2 Persistence and degradability:

| Identification | Degradability | | Biodegradability | |
|---|---------------|----------------|------------------|----------------|
| | | | | |
| Ethyl acetate CAS: 141-78-6 EC: 205-500-4 | BOD5 | 1,36 g O2/g | Concentration | 100 mg/L |
| | COD | 1,69 g O2/g | Period | 14 days |
| | BOD5/COD | 0,8 | % Biodegradable | 83 % |
| N-butyl acetate CAS: 123-86-4 EC: 204-658-1 | BOD5 | Non-applicable | Concentration | Non-applicable |
| | COD | Non-applicable | Period | 5 days |
| | BOD5/COD | Non-applicable | % Biodegradable | 84 % |

** Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -



SECTION 12: ECOLOGICAL INFORMATION ** (continued)

| Identification | Degradability | | Biodegradability | |
|--|---------------|----------------|------------------|----------------|
| | | | | |
| 2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9 | BOD5 | Non-applicable | Concentration | 785 mg/L |
| | COD | Non-applicable | Period | 8 days |
| | BOD5/COD | Non-applicable | % Biodegradable | 100 % |
| Xylene CAS: 1330-20-7 EC: 215-535-7 | BOD5 | Non-applicable | Concentration | Non-applicable |
| | COD | Non-applicable | Period | 28 days |
| | BOD5/COD | Non-applicable | % Biodegradable | 88 % |
| 2-ethylhexanoic acid, zirconium salt CAS: 22464-99-9 EC: 245-018-1 | BOD5 | Non-applicable | Concentration | 20 mg/L |
| | COD | Non-applicable | Period | 28 days |
| | BOD5/COD | Non-applicable | % Biodegradable | 99 % |
| Ethylbenzene CAS: 100-41-4 EC: 202-849-4 | BOD5 | Non-applicable | Concentration | 100 mg/L |
| | COD | Non-applicable | Period | 14 days |
| | BOD5/COD | Non-applicable | % Biodegradable | 90 % |

12.3 Bioaccumulative potential:

| Identification | Bioaccumulation potential | |
|---|---------------------------|----------|
| | | |
| Ethyl acetate CAS: 141-78-6 EC: 205-500-4 | BCF | 30 |
| | Pow Log | 0.73 |
| | Potential | Moderate |
| N-butyl acetate CAS: 123-86-4 EC: 204-658-1 | BCF | 4 |
| | Pow Log | 1.78 |
| | Potential | Low |
| Butane CAS: 106-97-8 EC: 203-448-7 | BCF | 33 |
| | Pow Log | 2.89 |
| | Potential | Moderate |
| Propane CAS: 74-98-6 EC: 200-827-9 | BCF | 13 |
| | Pow Log | 2.86 |
| | Potential | Low |
| Isobutane CAS: 75-28-5 EC: 200-857-2 | BCF | 27 |
| | Pow Log | 2.76 |
| | Potential | Low |
| Reaction mass of ethylbenzene and m-xylene and p-xylene CAS: Non-applicable EC: 905-562-9 | BCF | 9 |
| | Pow Log | 2.77 |
| | Potential | Low |

** Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -



SECTION 12: ECOLOGICAL INFORMATION ** (continued)

| Identification | Bioaccumulation potential | |
|--|---------------------------|------|
| | | |
| 2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9 | BCF | 1 |
| | Pow Log | 0.43 |
| | Potential | Low |
| Xylene CAS: 1330-20-7 EC: 215-535-7 | BCF | 9 |
| | Pow Log | 2.77 |
| | Potential | Low |
| 2-ethylhexanoic acid, zirconium salt CAS: 22464-99-9 EC: 245-018-1 | BCF | |
| | Pow Log | 2.96 |
| | Potential | |
| Ethylbenzene CAS: 100-41-4 EC: 202-849-4 | BCF | 1 |
| | Pow Log | 3.15 |
| | Potential | Low |

12.4 Mobility in soil:

| Identification | Absorption/desorption | | Volatility | |
|---|-----------------------|----------------------|------------|----------------------------------|
| | | | | |
| Ethyl acetate CAS: 141-78-6 EC: 205-500-4 | Koc | 59 | Henry | 13,58 Pa·m ³ /mol |
| | Conclusion | Very High | Dry soil | Yes |
| | Surface tension | 2,324E-2 N/m (25 °C) | Moist soil | Yes |
| N-butyl acetate CAS: 123-86-4 EC: 204-658-1 | Koc | Non-applicable | Henry | Non-applicable |
| | Conclusion | Non-applicable | Dry soil | Non-applicable |
| | Surface tension | 2,478E-2 N/m (25 °C) | Moist soil | Non-applicable |
| Butane CAS: 106-97-8 EC: 203-448-7 | Koc | 900 | Henry | 96258,75 Pa·m ³ /mol |
| | Conclusion | Low | Dry soil | Yes |
| | Surface tension | 1,187E-2 N/m (25 °C) | Moist soil | Yes |
| Propane CAS: 74-98-6 EC: 200-827-9 | Koc | 460 | Henry | 71636,78 Pa·m ³ /mol |
| | Conclusion | Moderate | Dry soil | Yes |
| | Surface tension | 7,02E-3 N/m (25 °C) | Moist soil | Yes |
| Isobutane CAS: 75-28-5 EC: 200-857-2 | Koc | 35 | Henry | 120576,75 Pa·m ³ /mol |
| | Conclusion | Very High | Dry soil | Yes |
| | Surface tension | 9,84E-3 N/m (25 °C) | Moist soil | Yes |
| Xylene CAS: 1330-20-7 EC: 215-535-7 | Koc | 202 | Henry | 524,86 Pa·m ³ /mol |
| | Conclusion | Moderate | Dry soil | Yes |
| | Surface tension | Non-applicable | Moist soil | Yes |

** Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -



SECTION 12: ECOLOGICAL INFORMATION ** (continued)

| Identification | Absorption/desorption | | Volatility | |
|--|-----------------------|--------------------------|------------|--------------------------------|
| | Koc | Non-applicable | Henry | 2,94E-1 Pa·m ³ /mol |
| 2-ethylhexanoic acid, zirconium salt CAS: 22464-99-9 EC: 245-018-1 | Conclusion | Non-applicable | Dry soil | Yes |
| | Surface tension | Non-applicable | Moist soil | Yes |
| | Koc | 520 | Henry | 798,44 Pa·m ³ /mol |
| Ethylbenzene CAS: 100-41-4 EC: 202-849-4 | Conclusion | Moderate | Dry soil | Yes |
| | Surface tension | 2,859E-2 N/m (25 °C) | Moist soil | Yes |
| | Koc | Non-applicable | Henry | Non-applicable |
| maleic anhydride CAS: 108-31-6 EC: 203-571-6 | Conclusion | Non-applicable | Dry soil | Non-applicable |
| | Surface tension | 1,673E-2 N/m (250,21 °C) | Moist soil | Non-applicable |
| | Koc | Non-applicable | Henry | Non-applicable |

12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

12.6 Other adverse effects:

Not described

** Changes with regards to the previous version

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

| Code | Description | Waste class (Regulation (EU) No 1357/2014) |
|-----------|---|--|
| 16 05 04* | gases in pressure containers (including halons) containing hazardous substances | Dangerous |

Type of waste (Regulation (EU) No 1357/2014):

HP3 Flammable, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP4 Irritant — skin irritation and eye damage

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommended disposal down the drain. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

- CONTINUED ON NEXT PAGE -



SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2021 and RID 2021:



- | | |
|---|---------------------|
| 14.1 UN number: | UN1950 |
| 14.2 UN proper shipping name: | AEROSOLS, flammable |
| 14.3 Transport hazard class(es): | 2 |
| Labels: | 2.1 |
| 14.4 Packing group: | N/A |
| 14.5 Environmental hazards: | No |
| 14.6 Special precautions for user | |
| Special regulations: | 190, 327, 344, 625 |
| Tunnel restriction code: | D |
| Physico-Chemical properties: | see section 9 |
| Limited quantities: | 1 L |
| 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code: | Non-applicable |

Transport of dangerous goods by sea:

With regard to IMDG 39-18:



- | | |
|---|-----------------------------|
| 14.1 UN number: | UN1950 |
| 14.2 UN proper shipping name: | AEROSOLS, flammable |
| 14.3 Transport hazard class(es): | 2 |
| Labels: | 2.1 |
| 14.4 Packing group: | N/A |
| 14.5 Marine pollutant: | No |
| 14.6 Special precautions for user | |
| Special regulations: | 63, 959, 190, 277, 327, 344 |
| EmS Codes: | F-D, S-U |
| Physico-Chemical properties: | see section 9 |
| Limited quantities: | 1 L |
| Segregation group: | Non-applicable |
| 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code: | Non-applicable |

Transport of dangerous goods by air:

With regard to IATA/ICAO 2021:



- | | |
|---|---------------------|
| 14.1 UN number: | UN1950 |
| 14.2 UN proper shipping name: | AEROSOLS, flammable |
| 14.3 Transport hazard class(es): | 2 |
| Labels: | 2.1 |
| 14.4 Packing group: | N/A |
| 14.5 Environmental hazards: | No |
| 14.6 Special precautions for user | |
| Physico-Chemical properties: | see section 9 |
| 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code: | Non-applicable |

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Regulation (EC) No 528/2012: contains a preservative to protect the initial properties of the treated article. Contains ethanol.

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

- CONTINUED ON NEXT PAGE -



SECTION 15: REGULATORY INFORMATION (continued)

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: Non-applicable

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Seveso III:

| Section | Description | Lower-tier requirements | Upper-tier requirements |
|---------|--------------------|-------------------------|-------------------------|
| P3a | FLAMMABLE AEROSOLS | 150 | 500 |

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Shall not be used in:

- ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- tricks and jokes,
- games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Contains Decamethylcyclotetrasiloxane, Octamethylcyclotetrasiloxane. 1. | Shall not be placed on the market in wash-off cosmetic products in a concentration equal to or greater than 0,1 % by weight of either substance, after 31 January 2020. | 2. | For the purposes of this entry, "wash-off cosmetic products" means cosmetic products as defined in Article 2(1)(a) of Regulation (EC) No 1223/2009 that, under normal conditions of use, are washed off with water after application.'

Occupational exposure to respirable crystalline silica must be controlled pursuant to Directive (EU) 2019/130.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION **

Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (Regulation (EC) No 2015/830).

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

** Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -



SECTION 16: OTHER INFORMATION ** (continued)

COMPOSITION/INFORMATION ON INGREDIENTS (SECTION 3, SECTION 11, SECTION 12):

- New declared substances
maleic anhydride (108-31-6)
- Removed substances
2-butanone oxime (96-29-7)
Titanium dioxide (aerodynamic diameter $\leq 10 \mu\text{m}$) (13463-67-7)

Substances that contribute to the classification (SECTION 2):

- New declared substances
N-butyl acetate (123-86-4)
- Removed substances
Reaction mass of ethylbenzene and m-xylene and p-xylene

Product contains PBT/vPvB substances (SECTION 2, SECTION 12):

- Removed substances
Decamethylcyclotetrasiloxane (541-02-6)
Octamethylcyclotetrasiloxane (556-67-2)

CLP Regulation (EC) No 1272/2008 (SECTION 2, SECTION 16):

- Pictograms
- Hazard statements
- Precautionary statements
- Supplementary information
- Substances contained in EUH208:
 - New declared substances
maleic anhydride (108-31-6)
 - Removed substances
2-butanone oxime (96-29-7)

Texts of the legislative phrases mentioned in section 2:

H336: May cause drowsiness or dizziness.
H317: May cause an allergic skin reaction.
H229: Pressurised container: May burst if heated.
H222: Extremely flammable aerosol.
H319: Causes serious eye irritation.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

Acute Tox. 4: H302 - Harmful if swallowed.
Acute Tox. 4: H312+H332 - Harmful in contact with skin or if inhaled.
Acute Tox. 4: H332 - Harmful if inhaled.
Aquatic Acute 1: H400 - Very toxic to aquatic life.
Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.
Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.
Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.
Eye Dam. 1: H318 - Causes serious eye damage.
Eye Irrit. 2: H319 - Causes serious eye irritation.
Flam. Gas 1A: H220 - Extremely flammable gas.
Flam. Liq. 2: H225 - Highly flammable liquid and vapour.
Flam. Liq. 3: H226 - Flammable liquid and vapour.
Press. Gas: H280 - Contains gas under pressure, may explode if heated.
Repr. 1B: H360 - May damage fertility or the unborn child.
Repr. 2: H361d - Suspected of damaging the unborn child.
Resp. Sens. 1: H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin Corr. 1B: H314 - Causes severe skin burns and eye damage.
Skin Irrit. 2: H315 - Causes skin irritation.
Skin Sens. 1: H317 - May cause an allergic skin reaction.
Skin Sens. 1A: H317 - May cause an allergic skin reaction.
STOT RE 1: H372 - Causes damage to organs through prolonged or repeated exposure (Inhalation).
STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Oral).
STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure.
STOT SE 3: H335 - May cause respiratory irritation.
STOT SE 3: H336 - May cause drowsiness or dizziness.

Classification procedure:

*** Changes with regards to the previous version*

- CONTINUED ON NEXT PAGE -



SECTION 16: OTHER INFORMATION ** (continued)

STOT SE 3: Calculation method
Skin Sens. 1A: Calculation method
Aerosol 1: Calculation method
Aerosol 1: Calculation method
Eye Irrit. 2: Calculation method

Advice related to training:

Minimal training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

<http://echa.europa.eu>
<http://eur-lex.europa.eu>

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road
IMDG: International maritime dangerous goods code
IATA: International Air Transport Association
ICAO: International Civil Aviation Organisation
COD: Chemical Oxygen Demand
BOD5: 5day biochemical oxygen demand
BCF: Bioconcentration factor
LD50: Lethal Dose 50
LC50: Lethal Concentration 50
EC50: Effective concentration 50
LogPOW: Octanolwater partition coefficient
Koc: Partition coefficient of organic carbon
UFI: unique formula identifier
IARC: International Agency for Research on Cancer

*** Changes with regards to the previous version*

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -