



MTN PRO 2K TWO COMPONENT VARNISH GLOSSY
Code: EX014PK900



Version: 2 Revision: 16/11/2018

Previous revision: 05/10/2018

Date of printing: 16/11/2018

SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1	PRODUCT IDENTIFIER:	MTN PRO 2K TWO COMPONENT VARNISH GLOSSY Code: EX014PK900
1.2	RELEVANT IDENTIFIED USES AND USES ADVISED AGAINST: <u>Intended uses (main technical functions):</u> Varnish. <u>Sectors of use:</u> Industrial manufacturing (SU3). Professional uses (SU22). <u>Uses advised against:</u> # This product is not recommended for any use or sector of use industrial, professional or consume other than those previously listed as 'Intended or identified uses'. This product is for the professional painting of vehicles only after reference to the manufacturer's data sheet. <u>Restrictions on manufacture, placing on market and use:</u> For professional users only. Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes.	[X] Industrial [X] Professional [] Consumers
1.3	DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET: MONTANA COLORS, S.L. Pol. Ind. Plà de les Vives - c/AnaisNin 6 - 08295 Sant Vicenç de Castellet (Barcelona) ESPAÑA Phone: +34 93 8332760 - Fax: +34 93 8332761 - www.montanacolors.com <u>E-mail address of the person responsible for the safety data sheet:</u> e-mail: msds@montanacolors.com	
1.4	EMERGENCY TELEPHONE NUMBER:	+34 93 8332787 (9:00-17:00 h.) (working hours)

SECTION 2 : HAZARDS IDENTIFICATION

2.1	CLASSIFICATION OF THE SUBSTANCE OR MIXTURE: <u>HMIS Hazard Ratings:</u>	<table border="1"> <tr><td>2</td><td>HEALTH</td></tr> <tr><td>4</td><td>FLAMMABILITY</td></tr> <tr><td>1</td><td>REACTIVITY</td></tr> <tr><td>G</td><td>PPE</td></tr> </table>	2	HEALTH	4	FLAMMABILITY	1	REACTIVITY	G	PPE	(2) Moderate health hazard (4) Very high flammability hazard (1) Low physicochemical hazard (G) Safety glasses, gloves and vapor respirator
2	HEALTH										
4	FLAMMABILITY										
1	REACTIVITY										
G	PPE										
Note: HMIS Hazard Ratings involve data and interpretations that may vary from company to company. They are intended only for rapid, general identification of the magnitude of the specific hazard. To deal adequately with the safe handling of the material, all the information contained in this SDS must be considered.											
<u>Hazard classification of the chemical:</u> DANGER: Flam. Aerosol 1:H222+H229 Eye Irrit. 2:H319 Skin Sens. 1:H317 STOTSE (narcosis) 3:H336 Aquatic Chronic 3:H412 EUH066											
<u>Danger class</u>	<u>Classification of the mixture</u>	<u>Cat.</u>	<u>Routes of exposure</u>	<u>Target organs</u>	<u>Effects</u>						
<u>Physicochemical:</u> 	Flam. Aerosol 1:H222+H229 Eye Irrit. 2:H319 Skin Sens. 1:H317	Cat.1 Cat.2 Cat.1 Cat.3	- Eyes Skin Inhalation	- Eyes Skin CNS	- Irritation Allergy Narcosis						
<u>Human health:</u> 	STOT SE (narcosis) 3:H336 Aquatic Chronic 3:H412 EUH066	Cat.3 -	- Skin	- Skin	- Dryness, Cracking						
<u>Environment:</u>											

Full text of hazard statements mentioned is indicated in section 16.

Note: When in section 3 a range of percentages is used, the health and environmental hazards describe the effects of the highest concentration of each component, but below the maximum value.

2.2	LABEL ELEMENTS: 	This product is labelled with the signal word DANGER
<u>Hazard statements:</u>		
H222	Extremely flammable aerosol.	
H229	Pressurized container: may burst if heated.	
H319	Causes serious eye irritation.	
H336	May cause drowsiness or dizziness.	
H317	May cause an allergic skin reaction.	
H412	Harmful to aquatic life with long lasting effects.	
EUH066	Repeated exposure may cause skin dryness or cracking.	
<u>Precautionary statements:</u>		
P101	If medical advice is needed, have product container or label at hand.	
P102	Keep out of reach of children.	
P103	Read label before use.	
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.	
P211	Do not spray on an open flame or other ignition source.	
P251	Do not pierce or burn, even after use.	
P271-P260d	Use only outdoors or in a well-ventilated area. Do not breathe aerosol.	
P363	Wash contaminated clothing before reuse.	
P305+P351+P338-P310	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.	



MTN PRO 2K TWO COMPONENT VARNISH GLOSSY
Code: EX014PK900



P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
P273-P501a Avoid release to the environment. Dispose of contents/container in accordance with local regulations.
Supplementary statements:
EUH204 Contains isocyanates. May produce an allergic reaction.
EUH208 Contains bis(12266-pentamethyl-4-piperidinyl) sebacate, 2,3-epoxypropyl neodecanoate. May produce an allergic reaction.
Substances that contribute to classification:
Acetone
n-butyl acetate
Hexamethylene diisocyanate, oligomers

2.3

OTHER HAZARDS:

Hazards which do not result in classification but which may contribute to the overall hazards of the mixture:
Other physicochemical hazards: Vapours may form with air a mixture potentially flammable or explosive.
Other adverse human health effects: People with hypersensitive respiratory tract (by instance, asthma or chronic bronchitis) should not handle this product. The symptoms in the respiratory tract may appear even last few hours of excessive exposure. The major dangers for respiratory ways are the dust, vapours or aerosols.
Other negative environmental effects: No other adverse effects are known.

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

3.1

SUBSTANCES:

Not applicable (mixture).

3.2

MIXTURES:

This product is a mixture.

Chemical description:

Aerosol.

INGREDIENTS:

40 < 50 % **Dimethyl ether**
 CAS: 115-10-6 , EC: 204-065-8
Danger: Flam. Gas 1:H220 | Press. Gas:H280

25 < 30 % **Acetone**
 CAS: 67-64-1 , EC: 200-662-2
Danger: Flam. Liq. 2:H225 | Eye Irrit. 2:H319 | STOT SE (narcosis) 3:H336 | EUH066

15 < 20 % **n-butyl acetate**
 CAS: 123-86-4 , EC: 204-658-1
Warning: Flam. Liq. 3:H226 | STOT SE (narcosis) 3:H336 | EUH066

2,5 < 5 % **Hexamethylene diisocyanate, oligomers**
 CAS: 28182-81-2 , EC: 500-060-2
Warning: Acute Tox. (inh.) 4:H332 | Skin Sens. 1:H317 | STOT SE (irrit.) 3:H335

2,5 < 5 % **Hydrocarbons C9 aromatics**
 (CAS: 64742-95-6) , List No. 918-668-5
Danger: Flam. Liq. 3:H226 | STOT SE (irrit.) 3:H335 | STOT SE (narcosis) 3:H336 | Asp. Tox. 1:H304 | Aquatic Chronic 2:H411 | EUH066

< 1 % **3-(2H-BTA-2-yl)propionic acid derivative**
 CAS: 127519-17-9 , EC: 407-000-3
Aquatic Chronic 2:H411

< 1 % **Bis(12266-pentamethyl-4-piperidinyl) sebacate**
 CAS: 41556-26-7 , EC: 255-437-1
Warning: Skin Sens. 1:H317 | Aquatic Acute 1:H400 | Aquatic Chronic 1:H410

< 0,15 % **2,3-epoxypropyl neodecanoate**
 CAS: 26761-45-5 , EC: 247-979-2
Warning: Skin Sens. 1:H317 | Muta. 2:H341o | Aquatic Chronic 2:H411

Impurities:

Does not contain other components or impurities which will influence the classification of the product.

Stabilizers:

None

Reference to other sections:

For more information on hazardous ingredients, see sections 8, 11, 12 and 16.



MTN PRO 2K TWO COMPONENT VARNISH GLOSSY
Code: EX014PK900



SECTION 4 : FIRST AID MEASURES

4.1 DESCRIPTION OF FIRST-AID MEASURES:



Symptoms may occur after exposure, so that in case of direct exposure to the product, when in doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. Lifeguards should pay attention to self-protection and use the recommended protective equipment if there is a possibility of exposure. Wear protective gloves when administering first aid.

Route of exposure	Symptoms and effects, acute and delayed	Description of first-aid measures
<u>Inhalation:</u> 	Inhalation of solvent vapours may produce headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, unconsciousness.	Remove the patient out of the contaminated area into the fresh air. If breathing is irregular or stops, administer artificial respiration. If the person is unconscious, place in appropriate recovery position. Keep the patient warm and at rest until medical attention arrives.
<u>Skin:</u> 	Skin contact causes redness. In case of prolonged contact, the skin may become dry.	Remove immediately contaminated clothing. Wash thoroughly the affected area with plenty of cold or lukewarm water and neutral soap, or use a suitable skin cleanser. Do not use solvents or thinners. In the case of skin reddening or rashes, contact a doctor immediately.
<u>Eyes:</u> 	Contact with the eyes produces redness and pain.	Remove contact lenses. Rinse eyes copiously by irrigation with plenty of clean, fresh water for at least 15 minutes, holding the eyelids apart, until the irritation is reduced. Call a physician immediately.
<u>Ingestion:</u>	If swallowed, may cause irritation of the throat, abdominal pain, drowsiness, nausea, vomiting and diarrhoea.	If swallowed, seek medical advice immediately and show container or label. Do not induce vomiting. Keep the patient at rest.

4.2 MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED:

The main symptoms and effects are indicated in sections 4.1 and 11

4.3 INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED:

Notes to physician: Treatment should be directed at the control of symptoms and the clinical condition of the patient.

Antidotes and contraindications: Specific antidote not known.

SECTION 5 : FIRE-FIGHTING MEASURES

5.1 EXTINGUISHING MEDIA:

Extinguishing powder or CO₂. In the case of more important fires, also alcohol resistant foam and water spray/mist. Do not use for extinguishing: direct water jet. Direct water jet may not be effective to extinguish the fire, since the fire may spread.

5.2 SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE:

Decomposes when heated intensely. Fire can produce a dense black smoke. As consequence of combustion or thermal decomposition, hazardous products may be produced: carbon monoxide, carbon dioxide, nitrogen oxides, isocyanate vapours, traces of hydrocyanic acid. Irritant. Exposure to combustion or decomposition products may be a hazard to health.



ANSI/NFPA 704:
Health: 2
Flammability: 4
Reactivity: 1
Special key: -

5.3 ADVICE FOR FIREFIGHTERS:

Special protective equipment: Depending on magnitude of fire, heat-proof protective clothing may be required, appropriate independent breathing apparatus, gloves, protective glasses or face masks and boots. If the fire-proof protective equipment is not available or not used, combat fire from a sheltered position or at a safe distance. The standard EN469 provides a basic level of protection for chemical incidents.

Other recommendations: Cool with water the tanks, cisterns or containers close to sources of heat or fire. Bear in mind the direction of the wind. Do not allow fire-fighting residue to enter drains, sewers or water courses.

SECTION 6 : ACCIDENTAL RELEASE MEASURES

6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES:

Eliminate possible sources of ignition and when appropriate, ventilate the area. Do not smoke. Avoid direct contact with this product. Avoid breathing vapours. Keep people without protection in opposition to the wind direction.

6.2 ENVIRONMENTAL PRECAUTIONS:

Avoid contamination of drains, surface or subterranean water and soil. In the case of large scale spills or when the product contaminates lakes, rivers or sewages, inform the appropriate authorities in accordance with local regulations.

6.3 METHODS AND MATERIAL FOR CONTAINMENT AND CLEANING UP:

Contain and mop up spills with non-combustible absorbent materials (earth, sand, vermiculite, diatomaceous earth, etc.). The contaminated area should be cleaned up immediately with a suitable decontaminant. One possible (flammable) decontaminant comprises: water, ethanol or isopropanol and concentrated ammonia solution (d=0,880) = 45/50/5 parts by volume. Another possible (non-flammable) decontaminant is made up of water and sodium carbonate = 95/5 parts by weight. Add the same decontaminant to any residues and allow to stand for several days in an un-sealed container until no further reaction occurs. Keep the remains in a closed container.



MTN PRO 2K TWO COMPONENT VARNISH GLOSSY
Code: EX014PK900



SECTION 7 : HANDLING AND STORAGE

- 7.1 **PRECAUTIONS FOR SAFE HANDLING:**
Comply with the existing legislation on health and safety at work.
General recommendations:
Avoid any type of leakage or escape.
Recommendations for the prevention of fire and explosion risks:
Pressurised container. Protect from sunlight and do not expose to temperature exceeding 50°C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Do not smoke.
- | | | |
|--|---|---------------------------|
| - Flash point | : | -39* °C |
| - Autoignition temperature | : | 321* °C |
| - Upper/lower flammability or explosive limits | : | 2.9* - 20.7 % Volume 25°C |
- Recommendations for the prevention of toxicological risks:**
People with a history of asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which isocyanate containing products are used. Do not eat, drink or smoke while handling. After handling, wash hands with soap and water. Avoid applying the product directly to people, animals, plants or foodstuffs. For exposure controls and personal protection measures, see section 8.
Recommendations for the prevention of environmental contamination:
Avoid any spillage in the environment. Pay special attention to the cleaning water. In the case of accidental spillage, follow the instructions indicated in section 6.
- 7.2 **CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES:**
Prevent unauthorized access. Keep out of reach of children. This product should be stored isolated from heat and electrical sources. Do not smoke in storage area. If possible, avoid direct contact with sunlight. Avoid extreme humidity conditions. Precautions should be taken to minimise exposure to atmospheric humidity or water, as carbon dioxide may be formed which, in closed containers can result in pressurisation. Care should be taken when re-opening partly used containers. Due to the sensitivity to humidity of the isocyanates, this product should be kept in the original container, or under pressure of dried nitrogen, for example. For more information, see section 10.
- | | | |
|-------------------------------|---|--|
| Class of store | : | According to current legislation. |
| Maximum storage period | : | 24. months |
| Temperature interval | : | # min: 5. °C, max: 40. °C (recommended). |
- Incompatible materials:**
Keep away from reducing agents, oxidizing agents, acids, alkalis. Clean the application equipment with a compatible solvent. Never leave the equipment filled with the cleaning solvent for prolonged periods, especially when used for cleaning solvents recovered which may contain moisture or alcohols, to prevent the product from hardening in the equipment, causing seals on the hoses or guns.
Type of packaging:
According to current legislation.



MTN PRO 2K TWO COMPONENT VARNISH GLOSSY
Code: EX014PK900



SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 CONTROL PARAMETERS:

If a product contains ingredients with exposure limits, may be necessary a personnel monitoring, work place or biological, to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to EN689, EN14042 and EN482 standard concerning methods for assessing the exposure by inhalation to chemical agents, and exposure to chemical and biological agents. Reference should be also made to national guidance documents for methods for the determination of dangerous substances.

OCCUPATIONAL EXPOSURE LIMIT VALUES (TLV)

AGCIH 2017	Year	TLV-TWA		TLV-STEL		Remarks
		ppm	mg/m3	ppm	mg/m3	
Dimethyl ether		1000.	1920.	-	-	Recommended
Acetone	2014	250.	594.	500.	1188.	A4 , BEI
n-butyl acetate	2015	50.	237.	150.	713.	
Hydrocarbons C9 aromatics		50.	290.	-	-	Recommended
3-(2H-BTA-2-yl)propionic acid derivative		-	0.15	-	-	Internal value
Bis(12266-pentamethyl-4-piperidiny) sebacate		-	1.0	-	-	Internal value

TLV - Threshold Limit Value, TWA - Time Weighted Average, STEL - Short Term Exposure Limit.

A4 - Non classified as carcinogenic in humans.

BEI - Biological exposure index (biological monitoring).

BIOLOGICAL EXPOSURE INDICES (BEI):

This preparation contains the following substances that have established a biological limit value:

- Acetone (2014): Biological determinant: acetone in urine, BEI: 25 mg/l, Sampling time: end of shift (2), Notation: (Ns).

(2) When the end of the exposition not coincide with the end of the working day, the sample will be taken as soon as possible after the real exposition ceases.

(Ns) Non-specific. The determinant is non-specific, since it is also observed after exposure to other chemicals.



MTN PRO 2K TWO COMPONENT VARNISH GLOSSY
Code: EX014PK900



8.2

EXPOSURE CONTROLS:**ENGINEERING MEASURES:**

Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these measures are not sufficient to maintain concentrations of particulates and vapours below the Occupational Exposure Limits, suitable respiratory protection must be worn.

Protection of respiratory system: Avoid the inhalation of vapours.

Protection of eyes and face: It is recommended to dispose of water taps, sources or eyewash bottles with clean water close to the working area.

Protection of hands and skin: It is recommended to dispose of water taps or sources with clean water close to the working area. Barrier creams may help to protect the exposed areas of the skin. Barrier creams should not be applied once exposure has occurred.

OCCUPATIONAL EXPOSURE CONTROLS: Directive 89/686/EEC-96/58/EC:

As a general measure on prevention and safety in the work place, we recommend the use of a basic personal protection equipment (PPE), with the corresponding EC marking. For more information on personal protective equipment (storage, use, cleaning, maintenance, type and characteristics of the PPE, protection class, marking, category, etc.), you should consult the informative brochures provided by the manufacturers of PPE.

Mask:

In order to obtain a suitable protection level, the filter class must be selected depending on the type and concentration of the contaminating agents present, in accordance with the specifications supplied by the filter producers. If the working area is insufficiently ventilated, when operators, whether spraying or not, are inside the spraybooth, compressed air-fed respiratory protective equipment (EN137) is required. For short periods of work, you can consider the utilisation of a combination mask with gas and particle filters, type A2-P2 (OSHA 29CFR 1910.134 and ANSI Z88.2).

Goggles:

Safety goggles with suitable lateral protection (OSHA 29CFR 1910.133). Clean daily and disinfect at regular intervals in accordance with the instructions of the manufacturer.

Face shield:

No.

Gloves:

Gloves resistant against chemicals (OSHA 29CFR 1910.132). There are several factors (for example, temperature), they do in practice the period of use of a protective gloves resistant against chemicals is clearly lower than the established standard OSHA 29CFR 1910.132. Due to the wide variety of circumstances and possibilities, we must have in mind the manual of instructions from manufacturers of gloves. Use the proper technique of removing gloves (without touching glove's outer surface) to avoid contact of the product with the skin. The gloves should be immediately replaced when any sign of degradation is noted.

Boots:

No.

Apron:

No.

Clothing:

Advisable.

Thermal hazards:

Not applicable (the product is handled at room temperature).

ENVIRONMENTAL EXPOSURE CONTROLS:

* Avoid any spillage in the environment of the product, wastes, packages or spraybooth sewages. Avoid any release into the atmosphere above the legal limits allowed.

Spills on the soil: Prevent contamination of soil.

Spills in water: Harmful to aquatic organisms. May cause long-term adverse effects on the aquatic environment. Do not allow to escape into drains, sewers or water courses.

Emissions to the atmosphere: Because of volatility, emissions to the atmosphere while handling and use may result. When possible, avoid solvent release to the atmosphere; do not pulverize more than is strictly necessary.

- VOC

:

888.5 g/l (-H₂O-es)

ASTM D-3960



MTN PRO 2K TWO COMPONENT VARNISH GLOSSY
Code: EX014PK900



SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

9.1	<p>INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES:</p> <p><u>Appearance</u> - Physical state : Aerosol. - Colour : Colourless. - Odour : Characteristic - Odour threshold : Not available (mixture).</p> <p><u>pH-value</u> - pH : Not applicable (non-aqueous media).</p> <p><u>Change of state</u> - Melting point : Not applicable (mixture). - Initial boiling point : Not applicable</p> <p><u>Density</u> - Vapour density : Not available - Relative density : 0.749* at 20/4°C Relative water</p> <p><u>Stability</u> - Decomposition temperature : Not available (technical impossibility to obtain the data).</p> <p><u>Viscosity:</u> - Viscosity (flow time) : Not applicable</p> <p><u>Volatility:</u> - Evaporation rate : Not applicable - Vapour pressure : Not available</p> <p><u>Solubility(ies)</u> - Solubility in water : # Not applicable - Liposolubility : Not applicable - Partition coefficient: n-octanol/water : Not applicable (mixture).</p> <p><u>Flammability:</u> - Flash point : -39* °C - Upper/lower flammability or explosive limits : 2.9* - 20.7 % Volume 25°C - Autoignition temperature : 321* °C</p> <p><u>Explosive properties:</u> Vapours can form explosive mixtures with air and are able to flame up or explode in presence of an ignition source.</p> <p><u>Oxidizing properties:</u> Not classified as oxidizing product.</p> <p>*Estimated values based on the substances composing the mixture.</p>
-----	--

9.2	<p>OTHER INFORMATION:</p> <p>- Solids : 6.3 % Weight - VOC (supply) : 93.7 % Weight</p> <p>The values indicated do not always coincide with product specifications. The data for the product specifications can be found in the technical data sheet of the same. For additional information concerning physical and chemical properties related to safety and environment, see sections 7 and 12.</p>
-----	--

SECTION 10 : STABILITY AND REACTIVITY

10.1	<p>REACTIVITY: <u>Corrosivity to metals:</u> It is not corrosive to metals. <u>Pyrophorical properties:</u> It is not pyrophoric.</p>
10.2	<p>CHEMICAL STABILITY: Stable under recommended storage and handling conditions.</p>
10.3	<p>POSSIBILITY OF HAZARDOUS REACTIONS: Possible dangerous reaction with water, oxidizing agents, acids, alkalis, amines, alcohols, peroxides. Exothermic reaction with amines and alcohols. Reacts with water under evolution of CO₂.</p>
10.4	<p>CONDITIONS TO AVOID: <u>Heat:</u> Keep away from sources of heat. <u>Light:</u> # If possible, avoid direct contact with sunlight. <u>Air:</u> The product is not affected by exposure to air, but should not be left the containers open. <u>Humidity:</u> Avoid humidity. Precautions should be taken to minimise exposure to atmospheric humidity or water, as carbon dioxide may be formed which, in closed containers can result in pressurisation. <u>Pressure:</u> Not relevant. <u>Shock:</u> The product is not sensitive to shocks, but as a recommendation of a general nature should be avoided bumps and rough handling to avoid dents and breakage of packaging, especially when the product is handled in large quantities, and during loading and download operations.</p>
10.5	<p>INCOMPATIBLE MATERIALS: Keep away from reducing agents, oxidizing agents, acids, alkalis. Clean the application equipment with a compatible solvent. Never leave the equipment filled with the cleaning solvent for prolonged periods, especially when used for cleaning solvents recovered which may contain moisture or alcohols, to prevent the product from hardening in the equipment, causing seals on the hoses or guns.</p>
10.6	<p>HAZARDOUS DECOMPOSITION PRODUCTS: As consequence of thermal decomposition, hazardous products may be produced, including isocyanates.</p>



MTN PRO 2K TWO COMPONENT VARNISH GLOSSY
Code: EX014PK900



SECTION 11 : TOXICOLOGICAL INFORMATION

No experimental toxicological data on the preparation is available. The toxicological classification for these mixture has been carried out by using the conventional calculation method of the Regulation (EU) No. 1272/2008~2017/776 (CLP).

11.1 INFORMATION ON TOXICOLOGICAL EFFECTS:ACUTE TOXICITY:Dose and lethal concentrations

for individual ingredients :

Dimethyl ether

Acetone

n-butyl acetate

Hexamethylene diisocyanate, oligomers

Hydrocarbons C9 aromatics

3-(2H-BTA-2-yl)propionic acid derivative

Bis(12266-pentamethyl-4-piperidiny) sebacate

2,3-epoxypropyl neodecanoate

DL50 (OECD 401)
mg/kg oral

5800. Rat

10768. Rat

> 5000. Rat

3592. Rat

> 2000. Rat

> 2000. Rat

9600. Rat

DL50 (OECD 402)
mg/kg cutaneous

15800. Rabbit

17600. Rabbit

> 5000. Rabbit

3160. Rabbit

> 2000. Rat

> 2000. Rat

3800. Rabbit

CL50 (OECD 403)
mg/m3.4h inhalation

> 100000 Rat

> 76000. Rat

> 23400. Rat

> 390. Rat

> 6193. Rat

> 250. Rat

No observed adverse effect level

Not available

Lowest observed adverse effect level

Not available

INFORMATION ON LIKELY ROUTES OF EXPOSURE :Acute toxicity:

Routes of exposure	Acute toxicity	Cat.	Main effects, acute and/or delayed
<u>Inhalation:</u> Not classified	ATE > 20000 mg/m3	-	Not classified as a product with acute toxicity if inhaled (based on available data, the classification criteria are not met).
<u>Skin:</u> Not classified	ATE > 2000 mg/kg	-	Not classified as a product with acute toxicity in contact with skin (based on available data, the classification criteria are not met).
<u>Eyes:</u> Not classified	Not available	-	Not classified as a product with acute toxicity by eye contact (lack of data).
<u>Ingestion:</u> Not classified	ATE > 5000 mg/kg	-	Not classified as a product with acute toxicity if swallowed (based on available data, the classification criteria are not met).

CORROSION / IRRITATION / SENSITISATION :

Danger class	Target organs	Cat.	Main effects, acute and/or delayed
<u>Respiratory corrosion/irritation:</u> Not classified	-	-	Not classified as a product corrosive or irritant by inhalation (based on available data, the classification criteria are not met).
<u>Skin corrosion/irritation:</u> Not classified	-	-	Not classified as a product corrosive or irritant in contact with skin (based on available data, the classification criteria are not met).
<u>Serious eye damage/irritation:</u> 	Eyes 	Cat.2	IRRITANT: Causes serious eye irritation.
<u>Respiratory sensitisation:</u> Not classified	-	-	Not classified as a product sensitising by inhalation (based on available data, the classification criteria are not met).
<u>Skin sensitisation:</u> 	Skin 	Cat.1	SENSITISING: May cause an allergic skin reaction.

ASPIRATION HAZARD:

Danger class	Target organs	Cat.	Main effects, acute and/or delayed
<u>Aspiration hazard:</u> Not classified	-	-	Not applicable.



MTN PRO 2K TWO COMPONENT VARNISH GLOSSY
Code: EX014PK900



SPECIFIC TARGET ORGANS TOXICITY (STOT): Single exposure (SE) and/or Repeated exposure (RE):

Effects	SE/RE	Target organs	Cat	Main effects, acute and/or delayed
<u>Cutaneous:</u>	RE	Skin 	-	DEFATTENING: Repeated exposure may cause skin dryness or cracking.
<u>Neurological:</u> 	SE	CNS 	Cat.3	NARCOSIS: May cause drowsiness or dizziness if inhaled.

CMR EFFECTS:

Carcinogenic effects: Is not considered as a carcinogenic product.

Genotoxicity: Is not considered as a mutagenic product.

Toxicity for reproduction: Do not harm fertility. Do not harm the fetus developing.

Effects via lactation: Not classified as a hazardous product for children breast-fed.

DELAYED AND IMMEDIATE EFFECTS AS WELL AS CHRONIC EFFECTS FROM SHORT AND LONG-TERM EXPOSURE:

Routes of exposure: May be absorbed by inhalation of vapour, through the skin and by ingestion.

Short-term exposure: Exposure to solvent vapour concentrations in excess of the stated occupational exposure limit, may result in adverse health effects, such as mucous membrane and respiratory system irritation and adverse effects on kidneys, liver and central nervous system. Liquid splashes in the eyes may cause irritation and reversible damage. May cause sensitization by skin contact. If swallowed, may cause irritation of the throat; other effects may be the same as described in the exposure to vapours.

Long-term or repeated exposure: Repeated or prolonged contact may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin. Repeated exposure may cause skin dryness or cracking.

INTERACTIVE EFFECTS:

Not available.

INFORMATION ABOUT TOXICOCINETICS, METABOLISM AND DISTRIBUTION:

Dermal absorption: Not available.

Basic toxicokinetics: Not available.

ADDITIONAL INFORMATION:

Based on the properties of the isocyanate content of this product and existing technical data of similar preparations, it can be concluded that respiratory exposure may cause acute irritation and/or sensitization of the respiratory system, resulting in asthmatic symptoms, wheezing and a tightness of the chest. Sensitised persons may subsequently show asthmatic symptoms when exposed to airborne concentrations of isocyanates well below the occupational exposure limit. Repeated exposure may lead to permanent respiratory disability. In case of prolonged contact, the skin can dry up and irritation could appear.

SECTION 12 : ECOLOGICAL INFORMATION

No experimental ecotoxicological data on the preparation as such is available. The ecotoxicological classification for these mixture has been carried out by using the conventional calculation method of the Regulation (EU) No. 1272/2008-2017/776 (CLP).

12.1	<u>TOXICITY:</u>	<u>CL50 (OECD 203)</u>		<u>CE50 (OECD 202)</u>		<u>CE50 (OECD 201)</u>	
		mg/L.96hours		mg/L.48hours		mg/L.72hours	
	<u>Acute toxicity in aquatic environment</u> for individual ingredients :						
	Dimethyl ether	4100.	Fishes	4400.	Daphnia		
	Acetone	5540.	Fishes	12100.	Daphnia		
	n-butyl acetate	18.	Fishes	44.	Daphnia	675.	Algae
	Hexamethylene diisocyanate, oligomers					> 1000.	Algae
	Hydrocarbons C9 aromatics	9.2	Fishes	3.2	Daphnia	2.9	Algae
	3-(2H-BTA-2-yl)propionic acid derivative	9.9	Fishes	3.2	Daphnia	2.0	Algae
	Bis(12266-pentamethyl-4-piperidinyl) sebacate	0.97	Fishes	20.	Daphnia		
	2,3-epoxypropyl neodecanoate	5.0	Fishes	4.8	Daphnia	3.5	Algae

No observed effect concentration

Not available

Lowest observed effect concentration

Not available

12.2 PERSISTENCE AND DEGRADABILITY:

Not available.

<u>Aerobic biodegradation</u> for individual ingredients :	<u>DQO</u> mgO2/g	<u>%DBO/DQO</u>			<u>Biodegradability</u>
		5 days	14 days	28 days	
Dimethyl ether	1041.	~ 1.	~ 3.	~ 5.	Not easy
Acetone	1920.			~ 91.	Easy
n-butyl acetate	2204.	~ 80.	~ 82.	~ 83.	Easy
Hexamethylene diisocyanate, oligomers					Not easy
Hydrocarbons C9 aromatics	3195.				Easy
3-(2H-BTA-2-yl)propionic acid derivative		2.	6.	9.	Not easy
Bis(12266-pentamethyl-4-piperidinyl) sebacate					Not easy
2,3-epoxypropyl neodecanoate				8.	Not easy

Note: Biodegradability data correspond to an average of data from various bibliographic sources.



MTN PRO 2K TWO COMPONENT VARNISH GLOSSY
Code: EX014PK900






12.3	BIOACCUMULATIVE POTENTIAL: Not available.			
	<u>Bioaccumulation</u> for individual ingredients :	<u>logPow</u>	<u>BCF</u> L/kg	<u>Potential</u>
	Dimethyl ether	0.0700	1.7 (calculated)	Not available
	Acetone	-0.240	3.2 (calculated)	Not available
	n-butyl acetate	1.81	6.9 (calculated)	Not available
	Hexamethylene diisocyanate, oligomers			Not available
	Hydrocarbons C9 aromatics	3.30	70. (calculated)	Not available
	3-(2H-BTA-2-yl)propionic acid derivative	9.20	> 1000. (calculated)	Not available
	Bis(12266-pentamethyl-4-piperidinyl) sebacate	2.37		Not available
	2,3-epoxypropyl neodecanoate	4.40	134. (calculated)	Not available
12.4	MOBILITY IN SOIL: Not available.			
	<u>Mobility</u> for individual ingredients :	<u>logKoc</u>	<u>Constante de Henry</u> Pa·m ³ /mol·20°C	<u>Potential</u>
	Dimethyl ether	0.890	101. (calculated)	Not available
	Acetone	0.990	3.0 (calculated)	Not available
	n-butyl acetate	1.84	29. (calculated)	Not available
	Hexamethylene diisocyanate, oligomers			Not available
	Hydrocarbons C9 aromatics	2.96	440. (calculated)	Not available
	3-(2H-BTA-2-yl)propionic acid derivative	5.42		Not available
	Bis(12266-pentamethyl-4-piperidinyl) sebacate	1.98		Not available
	2,3-epoxypropyl neodecanoate	2.83		Not available
12.6	OTHER ADVERSE EFFECTS: <u>Ozone depletion potential:</u> Not available. <u>Photochemical ozone creation potential:</u> Not available. <u>Earth global warming potential:</u> In case of fire or incineration liberates CO ₂ . <u>Endocrine disrupting potential:</u> Not available.			

SECTION 13 : DISPOSAL CONSIDERATIONS

13.1	WASTE TREATMENT METHODS: Directive 2008/98/EC--Regulation (EU) no. 1357/2014: Take all necessary measures to prevent the production of waste whenever possible. Analyse possible methods for revaluation or recycling. Do not discharge into drains or the environment, dispose of at an authorised waste collection point. Waste should be handled and disposed of in accordance with current local and national regulations. For exposure controls and personal protection measures, see section 8. <u>Disposal of empty containers:</u> Emptied containers and packaging should be disposed of in accordance with currently local and national regulations. The classification of packaging as hazardous waste will depend on the degree of emptying of the same, being the holder of the residue responsible for their classification, With contaminated containers and packaging, adopt the same measures as for the product in itself. Ensure the container is completely empty before throwing it away. <u>Procedures for neutralising or destroying the product:</u> In accordance with local regulations. Do not incinerate closed containers.
------	---

SECTION 14 : TRANSPORT INFORMATION

14.1	UN NUMBER: 1950
14.2	UN PROPER SHIPPING NAME: AEROSOLS
14.3 14.4	TRANSPORT HAZARD CLASS(ES) AND PACKING GROUP: <u>Transport by road (ADR 2017) and</u> <u>Transport by rail (RID 2017):</u> - Class: 2 - Packaging group: - - Classification code: 5F - Tunnel restriction code: (D) - Transport category: 2, max. ADR 1.1.3.6. 333 L - Limited quantities: 1 L (see total exemptions ADR 3.4) - Transport document: Consignment paper. - Instructions in writing: ADR 5.4.3.4 <u>Transport by sea (IMDG 38-16):</u> - Class: 2 (Division 2.1) - Packaging group: - - Emergency Sheet (EmS): F-D,S-U - First Aid Guide (MFAG): 620* - Marine pollutant: No. - Transport document: Shipping Bill of lading. <u>Transport by air (ICAO/IATA 2017):</u> - Class: 2 (Division 2.1) - Packaging group: - - Transport document: Air Bill of lading. <u>Transport by inland waterways (ADN):</u> Not available.

	MTN PRO 2K TWO COMPONENT VARNISH GLOSSY Code: EX014PK900	 
14.5	<u>ENVIRONMENTAL HAZARDS:</u> Not applicable.	
14.6	<u>SPECIAL PRECAUTIONS FOR USER:</u> Ensure that persons transporting the product know what to do in case of accident or spill. Always transport in closed containers that are upright and secure. Ensure adequate ventilation.	
14.7	<u>TRANSPORT IN BULK ACCORDING TO ANNEX II OF MARPOL 73/78 AND THE IBC CODE:</u> Not applicable.	

SECTION 15 : REGULATORY INFORMATION

15.1	<u>USA REGULATIONS:</u> - Occupational Safety and Health Act (OSHA): This product is considered to be hazardous under the OSHA Hazard Communication Standard. - Clean Air Act: · 112(r) Hazardous air pollutants (HAP) (40CFR 68): Dimethyl ether: Threshold quantity (TQ): 10000 lbs. The TQ applies to the quantity of substance in a release process, not at the facility as a whole. - Clean Water Act: · 307 Hazardous water priority pollutants (HWPP): No. - Comprehensive Environmental Response, Compensation and Liability Act (CERCLA): This product contains the following Hazardous Substances for Emergency release notification (40CFR 302): Acetone: Reportable quantity (RQ): 5000 lbs. n-butyl acetate: Reportable quantity (RQ): 5000 lbs. Releases of CERCLA hazardous substances, in quantities equal to or greater than their reportable quantity (RQ), are subject to reporting to the National Response Center under CERCLA. Such releases are also subject to state and local reporting under section 304 of Emergency Planning and Community Right-to-Know Act (EPCRA), also known as SARA Title III. - Superfund Amendments and Reauthorization Act (SARA Title III): · 302/304 Extremely Hazardous Substances (EHS) for Emergency release notification (40CFR 355): No. · 313 Reportable Ingredients (40CFR 372): No. · 311/312 Hazard Categories (40CFR 370): Yes. - Toxic Substance Control Act (TSCA): All chemical substances in this product comply with all applicable rules or order under TSCA. - California Proposition 65 (Safe Drinking Water and Toxic Enforcement Act of 1986): This product does not contain chemical substances known to the State of California to cause cancer or reproductive toxicity. <u>OTHER REGULATIONS:</u> <u>Other local legislations:</u> The receiver should verify the possible existence of local regulations applicable to the chemical.
------	---

SECTION 16 : OTHER INFORMATION

<u>TEXT OF THE PHRASES AND NOTES REFERENCED IN SECTIONS 2 AND/OR 3:</u> <u>Hazard statements according the Regulation (EU) No. 1272/2008-2017/776 (CLP), Anexo III:</u> H220 Extremely flammable gas. H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour. H280 Contains gas under pressure: may explode if heated. H304 May be fatal if swallowed and enters airways. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H332 Harmful if inhaled. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects. EUH066 Repeated exposure may cause skin dryness or cracking. H341o Suspected of causing genetic defects if swallowed. <u>Indications for preparations containing isocyanates:</u> Ready-to-use preparations containing isocyanates may have an irritant effect on mucous membranes -especially on breathing organs- and cause hypersensitivity reactions. Inhalation of vapour or spray mist may cause sensitisation. When handling preparations containing isocyanates all precautions required for solvent-containing preparations must be followed. Vapour and spray mist in particular should not be inhaled. Allergics and asthmatics, as well as people prone to respiratory ailments should not work with isocyanate-containing preparations. <u>ADVICES ON ANY TRAINING APPROPRIATE FOR WORKERS:</u> It is recommended for all staff that will handle this product to carry out a basic training in occupational risk and prevention, in order to provide understanding and interpretation of material safety data sheets and labelling of products as well. <u>MAIN LITERATURE REFERENCES AND SOURCES FOR DATA:</u> · European Chemicals Agency: ECHA, http://echa.europa.eu/ · Access to European Union Law, http://eur-lex.europa.eu/ · Industrial Solvents Handbook, Ibert Mellan (Noyes Data Co., 1970). · Threshold Limit Values, (ACGIH, 2016). · Riesgos y Patología por Isocianatos, G.Alomar (INSHT, DT.54.89, 1989). · ISOPA directives for the safety in the load/unload, transport and storage of TDI and MDI. ISOPA publication number: PSC-0014-GUIDL-EN. · European agreement on the international carriage of dangerous goods by road, (ADR 2017). · International Maritime Dangerous Goods Code IMDG including Amendment 38-16 (IMO, 2016). <u>ABBREVIATIONS AND ACRONYMS:</u> List of abbreviations and acronyms that can be used (but not necessarily used) in this material safety data sheet. <u>SAFETY DATA SHEET REGULATIONS:</u> Safety Data Sheet in accordance with the requirements of the OSHA Hazard Communication Standard, 29CFR 1910.1200.

HISTORY: **Revision:**
 Version: 1 05/10/2018

The information of this Safety Data Sheet is based on the present state of knowledge and on current UE and national laws, as the users' working conditions are beyond our knowledge and control. The product is not to be used for other purposes than those specified, without first obtaining written handling instruction. It is always the responsibility of the user to take all necessary steps in order to fulfil the demand laid down in the local rules and legislation. The information in this Material Safety Data Sheet is a descriptive document of the safety, physical and chemical properties of the product and is not intended to be used as a substitute for the product's Material Safety Data Sheet by a mark # in red and italic.