

## Información de producto | FICHA TÉCNICA

### ANTI-SLIP PAINT

400 ml, 10.72 Oz, 307 g. NET WT.

#### GENERAL DESCRIPTION

Transparent paint formulated with high quality, acrylic resins with non-slip textured finish. All-purpose use for any type of surface.

#### FEATURES

- Fast drying.
- Excellent elasticity.
- Easy to apply and repaint.
- Good adhesion to multiple surfaces.
- Does not contain lead.
- Strong resistance to wear.
- Class A3 in accordance to UNE-ENV 12633: 2003, Annex A.

#### APLICACIONES

Recommended for use on any metal, wood, or concrete surface where an anti-slip finish is required:

- Floors.
- Stairs.
- Ramps and entrances.
- Security.

#### INSTRUCTIONS FOR USE

- Shake the aerosol well before using, approximately for one minute after hearing the sound of the mixer.
- Apply to clean, dry surfaces. On rusty metallic surfaces remove rust with a wire brush.
- For best results apply in thin layers. Three thin layers are always better than one thick one, and may be repainted within ten minutes with the same paint.
- During application it is recommended to shake the spray can periodically.
- Never apply to equipment that is plugged in and use in well ventilated areas.
- Turn the aerosol upside down to clean out the valve after use. If te nozzle becomes blocked replace it with a new one.
- Request safety datasheets.

#### PHYSICAL PROPERTIES

Type of liant:	Acrylic
Color:	Transparent
Dry to the touch (ASTM D-1640 ISO 1517):	10'
Secado total (ASTM D-1640 ISO 1517):	2 h
Completely dry (ASTM D-1640 ISO 1517):	15 micras/capa
Adherence (ASTM D-3359 ISO 2409):	4B
Theoretical yield (continuous painting):	2 m <sup>2</sup> for 400 ml
Thinner:	Butyl acetate
Product life (Well Stored):	5 Years
Recoatable:	Después de 10'
Condition for application:	T° ambiente mínima 8°C
	T° superficie de 5°C a 50°C
	Humedad Máx. 85% R.H.P

Last date review:13/04/2016.

#### ATENCIÓN



#### APPEARANCE



#### LABEL



EX0141070 Imprimación Antideslizante

#### CAP SYSTEM



#### PACKAGING

Nominal capacity: 400 ml.  
Heat resistance of packaging: <50°C  
Propellant: DME

Box (6 units)  
205 X 140 X 200 mm.

