

## Product information | TECHNICAL DATA SHEET

### GRANITE EFFECT.

400 ml, 10,93 Oz, 310 g.

#### GENERAL DESCRIPTION

Decorative paint that gives a stone/granite appearance to all types of surfaces (metal, plastic, glass, polystyrene, etc.). To increase its adherence, apply a specific primer that is suitable for the surface being painted. Ideal for interiors. For exteriors we recommend adding a protective varnish to increase resistance.

#### CHARACTERISTICS

- Stone / granite-like appearance.
- Good adherence.
- Easy to apply and re-paint.
- UV resistant.

#### INSTRUCTIONS FOR USE

- Shake the spray can well before use for about one minute after hearing the sound of the mixer ball.
- Apply to clean, dry surfaces. Clean the surface with a degreaser or any other product that is suitable for concrete surfaces. On PP, apply a primer coat.
- Apply 1 or 2 coats to obtain the desired effect. Apply at a distance of 20-30 cm, allowing for a good distribution of the particles being applied to the surface.
- Do not apply to plugged-in electronic equipment and use in well-ventilated areas.
- Request safety data sheets.

#### PHYSICAL FEATURES

|  |                              |
|--|------------------------------|
| Binder type:                             | Mixture of resins            |
| Color:                                   | black-grey                   |
| Dry to the touch (ASTM D-1640 ISO 1517): | 1h                           |
| Total dry time (ASTM D-1640 ISO 1517):   | 24 h                         |
| Rendimiento teórico (pintado continuo):  | 0,5 m <sup>2</sup>           |
| May be repainted after:                  | 24h                          |
| Shelf life:                              | < 5 years (Correctly stored) |
| Resistance to heat:                      | 100°C                        |
| Application conditions:                  | Atmospheric temp.8°C         |
|  | Surface temp 5°-35 C         |
|  | Max. Humidity. 85% R.H.P     |

#### PACKAGING

Capacity 400 ml.  
Packaging heat resistance: <50°C  
Propellant: DME

Box (6 units)  
205 X 140 X 200 mm



#### APPLICATION

Can be used on all types of surfaces including metal, wood, plastics, polystyrene, stone and glass. To increase adherence in cases where necessary, apply a specific primer that is suitable for the surface being painted. May be used indoors. For outdoor use, apply a protective varnish to increase resistance to weathering.

#### IMAGE



#### LABEL



Negro / Black  
EX014PRO014

#### CAP SYSTEM



**Poltergeist Cap**  
Medio - Medium  
Válvula hembra - Female valve

