

Product information | TECHNICAL DATA SHEET

RUST EFFECT PAINT

400 ml, 10.4 Oz, 295 g.

GENERAL DESCRIPTION

Paint formulated with very fast-drying, thermoplastic acrylic resins combined with high quality pigments, to give an oxidized finish to any type of surface.

CHARACTERISTICS

- Very fast-drying.
- Easy to apply and repaint.
- Good coverage.
- Does not contain lead or heavy metals.
- Excellent flexibility.
- High outdoor durability.
- Good adhesion on a multitude of surfaces.

APPLICATION

Ideal for DIY and professional jobs on multiple surfaces: wood, metal, stainless steel, glass, wicker, plaster, ceramic, stone, fabric, paper, papier-mâché and hard plastic. On complicated surfaces use a primer or a perform a test prior to painting.

- DIY.
- Decoration.
- Art.

INSTRUCTIONS FOR USE

- Shake the spray can well before use for about one minute after hearing the sound of the mixer ball.
- Apply to clean, dry surfaces. Remove corrosion with a wire brush. For plastics such as PS and PP apply a primer coat first.
- Apply in thin coats to obtain better results. It is always better to apply three thin coats than one thick coat. Can be repainted after ten minutes with the same paint.
- Do not apply to plugged in electronic equipment and use in well ventilated areas.
- Request safety data sheets.

GENERAL DESCRIPTION

Brinder type	Thermoplastic acrylic
Color/Efecto:	Oxidized surface
Gloss (60°):	<5 %matt
Dry to touch (ASTM D-1640 ISO 1517):	< 10'
Total dry time (ASTM D-1640 ISO 1517):	2 h
Dry Coat Thickness (ASTM D-823 ISO 2808):	<15 µ/coat
Adherence (ASTM D-3359 ISO 2409):	B
Theoretical yield:	2,5 m ² para aerosol de 400 ml
Thinner:	Solvent mixture
Product shelf life:	< 5 años (Correctly stored)
Repainting:	After 15'
Paint resistance to heat:	120°C
Conditions for application:	Minimum atmospheric T°: 8°C
	Surface T°: 5-45°C
	Max. humidity: 85% R.H.P

*Adherence tests have been carried out on steel plates.

IMAGE



LABEL



Efecto Óxido / Rust Effect Paint
EX014PR0017

CAP SYSTEM



PACKAGING

Nominal capacity 400 ml.
Heat resistance of packaging: <50°C
Propellant: DME

Box (6 units)

205 X 140 X 200 mm

