



## Product information | TECHNICAL DATA SHEET

**Pocket. Solid Colors.** Low pressure, matt finishes.  
150ml, 4 Oz, 112 g

### GENERAL DESCRIPTION

Matt finish, very fast-drying alkyd enamel with excellent outdoor color durability.

### FEATURES

- Very fast drying.
- Good elasticity.
- Easy to apply and repaint.
- Hardens well.
- Does not contain lead nor other heavy metals.
- Good covering capability.
- Low pressure.
- Excellent resistance to the sun and rain.
- Long-lasting color.
- Very good resistance to UV light (see chart).
- Strong resistance to scratching once the film is polymerized.
- Its small size (150 ml) makes it a very practical tool.

### INSTRUCTIONS FOR USE

- Shake the aerosol well before using, approximately for one minute after hearing the sound of the mixer.
- Apply to clean, dry surfaces. On rusty metallic surfaces remove rust with a wire brush and prepare an anti-rust primer if considered necessary. Apply an anchor layer on plastics and polyesters.
- For best results apply in thin layers. Three thin layers are always better than one thick one, and may be repainted within fifteen minutes with the same paint.
- Turn the aerosol upside down to clean out the valve after use.  
If the nozzle becomes blocked replace it with a new one.
- Never apply to equipment that is plugged in and use in well ventilated areas.
- Request safety datasheets.

### PHYSICAL PROPERTIES

Type of liant:	Modified alkyd
Color:	See chart
Shine 60° (ASTM D-523 ISO 2813):	15-25% Matt
Dry to the touch (ASTM D-1640 ISO 1517):	10'
Completely dry (ASTM D-1640 ISO 1517):	24 h
Thickness of dry layer (ASTM D-823 ISO 2808):	15 micras/layer
Adherence (ASTM D-3359 ISO 2409):	0 B
Theoretical yield (continuous painting):	0,75 m <sup>2</sup> for 150 ml
Thinner:	Mixture
Product life:	(Well Stored) 10 years
Condition for application:	Minimum room temperature 8°C Surface temperature 5°C a 50°C Max humidity . 85% R.H.P
Heat resistance of paint:	100°C
Second coat:	After 15 'before 2 h or after 48

\* All of the adherence tests have been carried out on steel plates.

### APPLICATIONS

Due to the characteristics of this product we recommend its use for touch-ups and painting of all types of materials for either indoor or outdoor jobs. Suitable for home projects, crafts, fine arts, and generally where the properties of a high quality spray paint are required.

- Graffiti
- Gardening
- Fine Arts
- Construction
- DIY
- Sign painting
- Aluminum framing

### APPEARANCE



### LABEL



Opacity level    Outside endurance

### CAP SYSTEM



### PACKAGING

Low pressure.  
Nominal capacity: 150 ml.  
Heat resistance of packaging: <50°C  
Propellant: GLP – HC C<sub>3</sub>-C<sub>4</sub>

### COLORS

Amarillo Claro / Light Yellow EX0131021M	Azul Eléctrico / Electric Blue EX0130030M
Rojo Claro / Light Red EX0133020M	Negro / Black EX0133020M



## Product information | TECHNICAL DATA SHEET

**Pocket. Metallic Colors. Silver.**  
150ml, 4 Oz, 112 g

### GENERAL DESCRIPTION

The Pocket's metallic silver paint is formulated with fast-drying solvent-based acrylic resins and metallic inorganic pigments.

### FEATURES

- Low pressure.
- Very fast drying.
- Excellent adherence.
- Does not contain lead nor other heavy metals.
- Excellent metallic finish.
- Easy to apply and repaint with the same paint.
- May not be repainted or varnished with other paints.
- Non-resistant to abrasion.
- Low resistance to weathering.
- Does not contain anti-corrosive properties

### INSTRUCTIONS FOR USE

- Shake the aerosol well before using, approximately for one minute after hearing the sound of the mixer.
- Apply to clean, dry surfaces. On rusty metallic surfaces remove rust with a wire brush and prepare an anti-rust primer if considered necessary. Apply a primer coat on plastics and polyesters.
- For best results apply in thin coats. Three thin coats are always better than one thick one, and may be repainted within fifteen minutes with the same paint.
- Turn the aerosol upside down to clean out the valve after use.  
If the nozzle becomes blocked replace it with a new one.
- Never apply to equipment that is plugged in and use in well ventilated areas.
- Due to the nature of their pigments, these paints cannot be varnished or repainted with other solvent-based paints, except with Pocket paint.
- Request safety datasheets.

### PHYSICAL PROPERTIES

Basse pression:	Polyvalent female valve
Propulseur:	Butane / Propane / Mix
Type of liant:	Ketonic
Color:	Silver
Appearance:	Shine
Dry to the touch (ASTM D-1640 ISO 1517):	10'
Completely dry (ASTM D-1640 ISO 1517):	2 h
Thickness of dry layer (ASTM D-823 ISO 2808):	15 micras/layer
Adherence (ASTM D-3359 ISO 2409):	0 B
Theoretical yield (continuous painting):	1 m <sup>2</sup> for 150 ml
Thinner:	Mixture
Product life:	(Well Stored) 10 years
Condition for application:	Minimum room temperature 8°C Surface temperature 5°C a 50°C Max humidity . 85% R.H.P
Heat resistance of paint:	100°C

\* All of the adherence tests have been carried out on iron plates.

### APPLICATIONS

Provides the painted surfaces with a silver metallic appearance with great decorative power, very suitable for plastic and artistic arts for interior use, since its resistance to the weather is very low.

- DIY
- Graffiti
- Fine Arts
- Crafts/hobby
- Creative jobs
- Scenography

### APPEARANCE



### LABEL



### CAP SYSTEM



### COLOR



### PACKAGING

Low pressure.  
Nominal capacity 150 ml.  
Heat resistance of packaging: <50°C  
Propellant GLP – HC C<sub>3</sub>-C<sub>4</sub>

