

Product information | TECHNICAL DATA SHEET
STAINLESS STEEL HOME APPLIANCE PAINT
 400 ml, 10 Oz, 270 g.

GENERAL DESCRIPTION

Antioxidant coating formulated with acrylic resin and stainless steel metallic pigments. (Stainless Steel).

CHARACTERISTICS

- Excellent anticorrosive power.
- Protects the metallic foundation.
- Lead free.
- Good covering power.
- Very resistant to external temperatures.
- Excellent welding properties.
- High resistance to outdoor exposure.
- Can be recoated with the majority of enamels normally used.
- Ultra-fast drying.
- Good elasticity.

INSTRUCTIONS FOR USE

- Shake the spray can well before use for about one minute after hearing the sound of the mixer ball.
- Apply to clean, dry surfaces. On rusty metallic surfaces, remove rust with a wire brush and prepare an anti-rust primer if considered necessary. Apply an anchor layer on plastics and polyesters.
- For best results apply in thin layers. Three thin layers are always better than one thick one, and may be repainted within ten minutes with the same paint.
- Not suitable in the food industry for surfaces that are in contact with food.
- Turn the aerosol upside down to clean out the valve after use. If the nozzle becomes blocked replace it with a new one.
- Never apply to equipment that is plugged in and use in well ventilated areas.
- Request safety datasheets.

GENERAL DESCRIPTION

Binder type::	Thermoplastic acrylic
Color:	Red stainless steel
Dry to the touch (ASTM D-1640 ISO 1517):	10'
Total drying (ASTM D-1640 ISO 1517)	20'
Thickness of dry layer (ASTM D-823 ISO 2808):	<15 µ/capa (2 coats)
Adherence (ASTM D-3359 ISO 2409):	3B
Saline Mist	350 h
Pigment: Stainless Steel	C<0,03% - Cr 16-18 - Ni 10-14 - Mo 2-3%
Theoretical yield (continuous painting):	2 m ²
Recoating:	After 10'
Thinner:	Butyl Acetate
Product life:	< 5 años (Well Stored)
Heat resistance of paint:	300°C
Condiciones de aplicacion:	T° environment min 8°C
	T° surface min 5-50° C
	Humedad Máx. 85% R.H.P

* Adherence tests were performed on steel.

CAUTION



APPLICATION

- Washing machine paint.
- Refrigerator paint.
- DIY and gardening repairs.
- Extractor fan paint.
- Dishwasher paint.
- Painted outside ovens and microwave.

APPEARANCE



LABEL



CAP SYSTEM



PACKAGING

Nominal capacity 400 ml.
 Heat resistance of packaging: <50°C
 Propellant: DME

Box (6 units)
 205 X 140 X 200 mm

