

## Product information | TECHNICAL DATA SHEET

### ANTI-STAIN PAINT

500 ml, 15 Oz, 420 g.

#### GENERAL DESCRIPTION

Painting made with high quality acrylic resins together with titanium dioxide and additives to obtain a painting with a high covering power, ideal for covering tough stains in a fast and durable manner.

#### FEATURES

- Fast drying.
- White matt.
- Good adherence.
- Good covering power.
- Does not contain lead and other heavy metals.
- Easy to apply and recoat.
- High colour durability.
- Non-yellowing.

#### APPLICATIONS

Due to the characteristics of the product, we recommend its use for final finishing or as a background layer for other paintings.

- DIY
- Industrial applications
- Handicrafts
- Domestic

#### INSTRUCTIONS FOR USE

- Shake can vigorously for one minute after hearing mixer noise.
- Apply to clean, dry surfaces. On rusty metallic surfaces remove rust with a wire brush. Apply an anchor layer on plastics and polyesters.
- For best results apply in thin layers. Three thin layers are always better than one thick one, and may be repainted within five minutes with the same paint.
- After use, turn the aerosol upside down to clean out the valve. If the nozzle becomes blocked replace it with a new one.
- Disconnect the electrical appliance before painting.
- Use it in well ventilated areas.
- Request safety data sheets.

#### PHYSICAL PROPERTIES

Brinder type:	Thermoplastic acrylic
Color:	White
Brightness:	<10%
Dry to the touch (ASTM D-1640 ISO 1517):	5'
Total drying (ASTM D-1640 ISO 1517):	20'
Thickness of the dry coat:	20 µ/capa (2 applications)
theoretical Coverage ( pintado en continuo):	3 m <sup>2</sup>
Solvent:	Butyl Acetate
Product life:	(Well Stored) 2 years
Recoating:	After 5'
Paint heat resistance:	160°C
Application conditions:	T° environment min. 8°C
	T° Surface min 5-50°C
	Humidity max. 85% R.H.P

\* Adherence tests were performed on steel.

#### CAUTION



#### APPEARANCE



#### LABEL



EX015PR0987 Stain coverage

#### PACKAGING

Nominal Capacity: 500 ml  
Container heat resistance: <50°C  
Propellant: DME

Box (6 units)  
205 X 140 X 200 mm.

#### CAP SYSTEM

