

Product information | TECHNICAL DATA SHEET

**BATHTUBS & TILE PAINT**

400 ml, 11,7 Oz, 331 g.

**GENERAL DESCRIPTION**

White paint with a satin finish developed with modified epoxy resins. Ideal for touching up or repainting bathtubs, sinks and tiles in one step.

Its high resistance to humidity and extremely strong adherence makes this product ideal for renovating bathrooms or kitchens, optimally renovating any porcelain or ceramic surface.

The product is only available in white and can be painted over with a varnish or paint to modify the level of gloss in finish or the color.

**CHARACTERISTICS**

- Good adhesion to ceramic and porcelain.
- Strong resistance in humid environments.
- Resistant to UV rays.
- Easy to apply.
- Satin white color. Can be painted over with other paints and varnishes.

**APPLICATION**

The paint can be applied to ceramic and porcelain surfaces facilitating a variety of renovation projects

- Decoration
- DIY
- Scenography
- Maintenance of sports facilities and hospitality

**INSTRUCTIONS FOR USE**

- Shake the can very well before use, for about a minute after hearing the noise of the mixing ball.
- Apply to clean and dry surfaces, removing mold, grease, soap residue and any other kind of dirt. Prepare the surface with an scrubbing sponge and bathroom cleaning solution to create a slightly porous surface for better adhesion. Clean the entire surface once again and rinse with water. Sand the whole surface with P400 or P600 grit wet / dry sandpaper. Clean and dry before painting.
- Apply the product from a distance of 15-20 cm. Apply in thin layers to avoid paint build up. Three thin coats are always better than one thick layer. Always test product on a small area before painting.
- The surface can be painted again with the same product after 30-60 minutes. You can apply other products after 24 hours. After 72 hours you can use the bathtub normally.
- Once the application is finished, invert the aerosol and purge the valve after use. If the nozzle clogs, replace it with a new one.
- Do not apply to equipment connected to the mains and use in well ventilated areas.
- Request safety data sheets.

**GENERAL DESCRIPTION**

Binder type:	Mix of epoxy resins
Color:	White
Brightness (60°):	10-20%
Dry to the touch (ASTM D-1640 ISO 1517):	30-60'
Total dry time (ASTM D-1640 ISO 1517):	72 h
Theoretical performance:	1.5 m <sup>2</sup> per 400 ml
Diluent:	Solvent mix
Theoretical performance (continuous painting):	1-1,25 m <sup>2</sup> ; 2 coats (60 μ) 0,6-0,75 m <sup>2</sup>
Repainting:	With the same product after 30-60'
	With other paints or varnishes, after 24 h. Sand beforehand (P400 / P600)
Shelf life:	5 years (Correctly stored)
Heat resistance of paint:	100°C
Condiciones de aplicacion:	Ambient temperature 8°C
	Surface temperature 5-40°C
	Humidity Max. 85% R.H.P

280421

**IMAGE**



**LABEL**



Blanco / White  
EX014PR0015

**CAP SYSTEM**



**PACKAGING**

Capacity 400 ml.  
Packaging heat resistance: <50°C  
Propellant: DME

**Box (6 units)**  
205 X 140 X 200 mm

