

Product information | TECHNICAL DATA SHEET

CONTACT ADHESIVE. Highly adhesive. Non-removable.
400 ml, 10.2 Oz , 298,8 g.

GENERAL DESCRIPTION

Adhesive resin mixed with aliphatic solvents, with a high adhesive power.

FEATURES

- Adhesive Contact.
- Immediate adhesion.
- Excellent adhesion.
- Doesn't deteriorate materials.
- Apply pressure to the joint.
- Not suitable for applications in vehicle headliner.

APPLICATIONS

Film forming adhesive with immediate and high adhesion. Especially adapted for different automotive* applications and DIY. The most suitable materials for bonding are:

- Polyurethane and polyethylene foams
- Fibers
- Cork
- Cardboard
- Paper
- Carpet

* **Not recommended** for gluing objects to car ceilings. (High temperatures caused by the sun plus the object's weight do not make for a good result)

INSTRUCTIONS FOR USE

- Before using, shake the aerosol vigorously for approximately one minute after the noise of the mixer starts.
- Apply over clean and dry surfaces. On rusty metallic surfaces: Remove corrosion with a wire brush. In plastics like PS and PP apply first a primer layer. See product's behavior in any plastic surface.
- Hold the aerosol upside down after use to purge the valve. If the nozzle is blocked, replace it with a new one.
- Do not apply on plugged-in electrical equipment and use in well-ventilated areas.
- Ask for MSDS.

PHYSICAL PROPERTIES

Color:	Transparent yellowish
Hardening:	10-60 minuts
Application temperature:	10-60°C
Maximum exposure temperature:	40°C
Theoretical yield (continuous painting):	2m ²
Solvent:	Hexano
Product life:	(Well Stored) 5 years

*The adhesion tests were done on PP (EPDM modified).

150121



APPEARANCE



LABEL



EX014PR0801 Adhesive

CAP SISTEM



PACKAGING

Nominal capacity 400 ml.
Heat resistance of packaging: <50°C
Propellant: DME

Box (6 units)
205 X 140 X 200 mm.

