

Product information | TECHNICAL DATA SHEET

CONTACT ADHESIVE. Highly adhesive. Non-removable.
400 ml, 10.2 Oz , 298,8 g.

GENERAL DESCRIPTION

Adhesive resin mixed with aliphatic solvents, with a high adhesive power.

FEATURES

- Adhesive Contact.
- Immediate adhesion.
- Excellent adhesion.
- Doesn't deteriorate materials.
- Apply pressure to the joint.
- Not suitable for applications in vehicle headliner.

APPLICATIONS

Film forming adhesive with immediate and high adhesion. Especially adapted for different automotive* applications and DIY. The most suitable materials for bonding are:

- Polyurethane and polyethylene foams
- Fibers
- Cork
- Cardboard
- Paper
- Carpet

* **Not recommended** for gluing objects to car ceilings. (High temperatures caused by the sun plus the object's weight do not make for a good result)

INSTRUCTIONS FOR USE

- Before using, shake the aerosol vigorously for approximately one minute after the noise of the mixer starts.
- Apply over clean and dry surfaces. On rusty metallic surfaces: Remove corrosion with a wire brush. In plastics like PS and PP apply first a primer layer. See product's behavior in any plastic surface.
- Hold the aerosol upside down after use to purge the valve. If the nozzle is blocked, replace it with a new one.
- Do not apply on plugged-in electrical equipment and use in well-ventilated areas.
- Ask for MSDS.

PHYSICAL PROPERTIES

| | |
|--|-----------------------|
| Color: | Transparent yellowish |
| Hardening: | 10-60 minutes |
| Application temperature: | 10-60°C |
| Maximum exposure temperature: | 40°C |
| Theoretical yield (continuous painting): | 2m ² |
| Solvent: | Hexane |
| Product life: | (Well Stored) 5 years |

*The adhesion tests were done on PP (EPDM modified).

030621



IMAGE



LABEL



Adhesivo Contacto / Contact Adhesive
EX014PRO801

CAP SYSTEM



PACKAGING

Nominal capacity 400 ml.
Heat resistance of packaging: <50°C
Propellant: DME

Box (6 units)
205 X 140 X 200 mm.

