

Product information | TECHNICAL DATA SHEET

GOTELÉ - Wall Texture

400 ml, 475 g NET, 16,76 Oz.

GENERAL DESCRIPTION

Product formulated on the basis of an exclusive polyurethane dispersion to imitate the stucco texture in an easy and simple way. Ideal for the renovation and repair of this type of stucco.

FEATURES

- Easy and comfortable way to obtain a stucco-type finish.
- Easy to repaint with all types of acrylic paints.
- Does not contain lead or other heavy metals.
- May be used indoors.

INSTRUCTIONS FOR USE

- Shake the can vigorously before use, for approximately one minute after hearing the sound of the mixer.
- Apply to clean, dry surfaces. If there are stains on the surface before application, first apply an MTN Industrial Anti-stain Spray as a primer coat.
- We recommend doing a preliminary test on a disposable surface to practice spraying.
- Depending on the distance of application and the thickness of the layer, thin or thick finishes may be obtained. The atmospheric and aerosol temperature itself during application may also influence the type of texture obtained.
- Wait between 10-20 minutes before coats. Before painting with acrylic paint, allow to dry between 6-12 hours.
- Invert the aerosol in order to purge the valve after use. Take off the nozzle and clean with tap water. In the case of nozzle clogging, replace with a new one.
- Never apply to equipment that is plugged in and use in well ventilated areas.
- Request safety datasheets.

PHYSICAL PROPERTIES

Brinder type:	PU
Color:	White
Shine (60°):	<10
Dry to the touch (ASTM D-1640 ISO 1517):	30'
Total drying (ASTM D-1640 ISO 1517):	12 h
Coat thickness (ASTM D-823 ISO 2808):	20 microns/coat
Theoretical yield (continuous painting):	1,5m ² for 400 ml aerosol
Thinner:	Water
Product life:	(Well Stored) 5 Years
Repainting:	After 10-20' with the paint itself. With other paints, after 6-12h
Application conditions:	T° environment min. 8°C T° surface min. 5-50°C Humidity Max. 85% R.H.P

* Performance will depend on the texture you wish to obtain. Last revision date: 20/02/2017.

CAUTION



APPLICATIONS


The product may be applied to a multitude of surfaces such as concrete, drywall, plaster board or wood. Product can be repainted with all types of wall paints. Recommended for:

- Construction.
- Painting professionals.
- DIY.

APPEARANCE



LABEL



EX014PG100 Stipple

CAP SYSTEM



PACKAGING

Nominal Capacity: 400 ml.
Container heat resistance: <50°C
Propellant: DME

Box (6 units)
205 X 140 X 200 mm.

