

Product information | TECHNICAL DATA SHEET

MARBLE EFFECT PAINT

400 ml, 10.34 Oz, 293 g.

GENERAL DESCRIPTION

Decorative solvent-based acrylic paint that gives a marble-like appearance to all kinds of surfaces. Thanks to its characteristics, it can be applied to metal, most plastics, stone, ceramics, glass or other painted surfaces.

The paint has an excellent opacity and expands on the surface by means of fine threads of colored lacquer, simulating the "veins" of marble. Certain surfaces may require a specific primer to increase adhesion. Ideal for interior and exterior finishes, we recommend adding protective varnish to improve its resistance.

CHARACTERISTICS

- Very fast drying.
- Marble appearance.
- Colored lacquer threads or veins.
- Recoatable. Compatible with MTN Hardcore, MTN 94 and MTN PRO colors / primers / varnishes.
- Good adhesion on most surfaces.
- Easy to apply and recoat.
- Resistant to UV rays.

APPLICATION

The paint can be perfectly combined with other MTN brand products such as 94, Hardcore, Water Based or MTN PRO Color Paint. The product is available in black, white, gold and silver, thus meeting most creative needs. On non-porous materials, it requires a primer layer or test spray on a hidden part of the object.

- Decoration
- DIY
- Crafts
- Fine arts

INSTRUCTIONS FOR USE

- Before use, shake the can very well for about a minute after hearing the noise of the mixing ball.
- Apply to clean and dry surfaces. Clean the surface with a degreaser or any other specific product for the particular surface. On PP, PE, PA, ceramics or glass, apply a base coat or specific paint color suitable for these surfaces. On other paints, apply according to their recoating conditions. We recommend testing the product on a hidden area. Apply after 30' - 2 hours on paints such as MTN Hardcore and 94. On MTN PRO Color Paint apply after 15-30'.
- If the application of a varnish is necessary, follow the recoating times of the base product.
- After use, invert the aerosol and purge the valve. If the nozzle clogs replace it with a new one.
- Do not apply to equipment connected to the mains and use in well ventilated areas.
- Safety data sheets are available.

GENERAL DESCRIPTION

Binder Type:	Acrylic solvent
Color / Effect:	Black, White, Silver, Gold
Dry to touch (ASTM D-1640 ISO 1517):	15-30'
Totally dry (ASTM D-1640 ISO 1517):	12 h
Theoretical performance *(continuous painting):	1-4 m ² per 400 ml aerosol
Recoating:	15-30' without previous primer paint
	With previous primer paint, follow recoating times of the previous product
Product life:	5 years (stored correctly)
	Resistance of the paint to heat: 100°C
Application conditions:	Ambient temperature 8°C
	Surface temperature 5-40°C
	Humidity Max. 85% R.H.P

* Depending on the desired effect.

280421

IMAGE



LABEL



CAP SYSTEM



PACKAGING

Capacity 400 ml.
Packaging heat resistance: <50°C
Propellant: DME

Box (6 units)
205 X 140 X 200 mm

