

## Product information | TECHNICAL DATA SHEET

### MARKING PAINT

500 ml, 13 Oz, 360 g.

#### GENERAL DESCRIPTION

Paint composed of acrylic resins and high quality copolymers of a thermoplastic nature, specially designed for temporary marking.

#### FEATURES

- Fast drying.
- Very bright colors.
- Easy to apply.
- Resists freezing temperatures.
- Does not contain lead nor other heavy metals.
- Can be used on numerous materials.
- Se puede eliminar fácilmente con acetona o con agua caliente.
- Good adhesion.
- Can be removed easily with acetone or hot water.
- Its flexible valve allows for application with one finger.

#### APPLICATIONS

Due to the characteristics of the product, we recommend its use for construction and road work marking in the following applications:

- Road work
- Topographical Signals
- Mining
- Industry
- Geological studies
- Construction
- In general where temporary, highly visible signage is necessary

#### INSTRUCTIONS FOR USE

- Shake the aerosol well before using, approximately for one minute after hearing the sound of the mixer.
- Product can be applied in any position due to its 360° technology
- Never apply to equipment that is plugged in and use in well ventilated areas.
- Request safety datasheets.

#### PHYSICAL PROPERTIES

Binder type:	Thermoplastic Acrylic
Color:	See chart
Shine:	<10%
Dry to the touch (ASTM D-1640 ISO 1517):	5'
Completely dry (ASTM D-1640 ISO 1517):	10'
Thickness of dry layer (ASTM D-823 ISO 2808):	40 micras/layer
Adherence (ASTM D-3359 ISO 2409):	2B
Theoretical yield (continuous painting):	2,3 m <sup>2</sup>
Thinner:	Butyl Acetate
Product life:	(Well Stored) 5 Years
Heat resistance of paint:	150°C
Condition for application:	Minimum room temperature 8°C Surface temperature 5-50°C Max humidity 85% R.H.P

\* Adherence tests were performed on steel.

#### CAUTION



#### APPEARANCE

##### DONUT

Indicates the paint color.



1. Shake can before use.
2. Remove safety piece from plastic cap.
3. Invert can to paint 360°
4. Detalle del tapón.

#### LABEL



EX015PR0402	Yellow	EX015PR0404	Red	EX015PR0436	Green
EX015PR0433	Orange	EX015PR0405	Magenta	EX015PR0437	Blue

#### PACKAGING

Nominal capacity 500 ml.  
Heat resistance of packaging: <50°C  
Propellant: DME

Box (6 units)  
205 X 140 X 200 mm.

