

Product information | TECHNICAL DATA SHEET

ROAD SIGNAGE PAINT

750 ml, 11 Oz, 318 g.

GENERAL DESCRIPTION

Very fast-drying alkyd enamel paint, ideal for long-lasting exterior color and for obtaining the perfect finish for painting road markings.

FEATURES

- Fast drying.
- Very vibrant colors.
- Easy to apply.
- Does not contain lead nor other heavy metals.
- May be used on a multitude of materials.
- Excellent adherence on concrete and asphalt.
- Great durability of the pigments.
- Strong resistance to the sun and rain.
- Good covering capability.
- Width: 6-12 cm. Length. Between 35-55 m, depending on the speed of application and the porosity of the surface.
- May be used with machines or road marking machines.
- Allows for posterior application of reflective glass beads.

INSTRUCTIONS FOR USE

- Shake the aerosol well before using, approximately for one minute after hearing the sound of the mixer.
- Road marking machines allow for easy, simple painting of straight lines, and make it possible to modify the width and length of the line.
- May be used for interior and exterior application.
- Apply to clean, dry surfaces.
- May be repainted between 30 minutes to 2 hours afterwards. May be repainted after 24-48 h.
- If working manually, paint with the can in an upright, inverted position.
- Never apply to equipment that is plugged in and use in well ventilated areas.
- Request safety datasheets.

PHYSICAL PROPERTIES

Type of liant:	Alkyd
Color:	See chart
Shine:	<10%
Dry to the touch (ASTM D-1640 ISO 1517):	30'
Completely dry (ASTM D-1640 ISO 1517):	2h
Thickness of dry layer (ASTM D-823 ISO 2808):	40 µ/layer (2 coats)
Adherence (ASTM D-3359 ISO 2409):	2B
Theoretical yield (continuous painting):	50-80 m
Thinner:	Butyl acetate
Product life:	(Well Stored) >5 years
Repainted:	After 30' and before 2h after 24-48h
Resistencia al calor:	150°C
Condition for application:	Minimum room temperature 8°C Surface temperature 5°C a 50°C Max humidity 85% R.H.P

* All of the adherence tests have been carried out on steel plates.

APPLICATIONS

Due to its characteristics, this product is ideal for road markings:

- Industry
- Boundary markings
- Road work
- Construction
- Road signage, parking lots
- In general where permanent, horizontal marking is required

APPEARANCE



LABEL



PACKAGING

Nominal capacity 750 ml.
Heat resistance of packaging: <50°C
Propellant: DME


Box (6 units)
205 X 140 X 200 mm.



COLORS



EX017PR0426 White



EX017PR0425 Yellow

CAUTION

