

## Información de producto | FICHA TÉCNICA

### WASH PRIMER

400 ml, 10.9 Oz, 309 g. NET WT.

#### GENERAL DESCRIPTION

Phosphate Primer (Wash Primer) with excellent adhesion on galvanized and zinc electroplated steel, aluminum, and all types of polished metals. Also works very well as a primer layer on some plastics.

#### FEATURES

- Fast drying.
- Easy to apply and repaint.
- Good adherence.
- Does not contain lead.

#### APPLICATIONS

Recommended to be utilized as a primer layer on galvanized metal surfaces such as:

- Garage doors or metal shutters.
- Copper pipes.
- Aluminum profiling.

Also usable as a primer on polyamide 6 plastic surfaces, carbon fiber, epoxy, polyester, acrylate, PVC, PC, and ABS. The product's characteristics make it very adequate on pre-sanded surfaces painted with polyester-type paints (aluminum profiling) or on 2K epoxy.

#### INSTRUCTIONS FOR USE

- Shake the aerosol well before using, approximately for one minute after hearing the sound of the mixer.
- Apply to clean, dry surfaces. On rusty metallic surfaces remove rust with a wire brush. Due to the multitude of substrates and methods for application, it is recommended to do a test on the material prior to application.
- Apply in thin, even layers to obtain the best results. Second coat may be applied after 20 mins. May be repainted with other products after 2 hours. Check compatibility by testing.
- Never apply to equipment that is plugged in and use in well ventilated areas.
- Request safety datasheets.

#### PHYSICAL PROPERTIES

Type of liant:	Resin mixture
Color:	Grey
Dry to the touch (ASTM D-1640 ISO 1517):	20'
Completely dry (ASTM D-1640 ISO 1517):	2 h
Thickness of dry layer (ASTM D-823 ISO 2808) :	7-15 micras/layer
Adherence (ASTM D-3359 ISO 2409):	B
Theoretical yield (continuous painting):	2 m <sup>2</sup> for 400 ml
Thinner:	Solvent mixture
Product life:	(Well Stored) 5 Years
Condition for application:	Minimum room temperature 8°C Surface temperature 5°C a 50°C Max humidity, 85% R.H.P

\* Adhesion tests have been carried out on galvanized steel plates. Fecha última revisión: 14/01/2016.

#### CAUTION



#### APPEARANCE



#### LABEL



EX014PR0133 Wash Primer

#### CAP SYSTEM



#### PACKAGING

Nominal capacity 400 ml.  
Heat resistance of packaging: <50°C  
Propellant: DME

Box (6 units)  
205 X 140 X 200 mm.

