

## Product information | TECHNICAL DATA SHEET

**EPS PRIMER (STYROFOAM).** Prepares and primes surfaces to be painted.  
400 ml, 11.8 Oz, 334 g.

### GENERAL DESCRIPTION

Grey acrylic primer that brings to expanded polystyrene surfaces a protection that allows post-painted with solvent based paints.

### FEATURES

- Very fast drying.
- Easy to apply and recoat.
- Doesn't content lead.
- Perfect adhesion.
- Good coverage and filling capability.

### APPLICATIONS

Indicated, as a primer layer to protect the expanded polystyrene in:

- Modeling
- Crafts
- Layouts
- Architectural Studies

### INSTRUCTIONS FOR USE

- Before using, shake the aerosol vigorously for approximately one minute after the noise of the mixer starts. Paint with the container upright. Apply quick and fine layers at a distance of about 20 cm past.
- To obtain a perfect protection of the expanded polystyrene, it is important to cover accurately the whole surface, preventing unpainted pores or spaces. We recommend applying a minimum of 5 thin layers, leaving 5-10 minute drying intervals between each layer.
- Once dry for 30 min apply any type of paint, hence avoiding any damage to the polystyrene.
- Don't spray on plugged-in equipment and use it only in well ventilated areas.
- Ask for MSDS.

### PHYSICAL PROPERTIES

Binder:	Acrylic
Color:	Grey R.7001
Dry to touch ( ASTM D-1640 ISO 1517 ):	10'
Total drying ( ASTM D-1640 ISO 1517 ):	30'
Dryfilm thickness ( ASTM D-823 ISO 2808 ):	10-15 µ/layer (2pasadas)
Adherence (ASTM D-3359 ISO 2409 ):	n/a
Theoretical yield ( pintado en continuo ):	2 m <sup>2</sup>
Thinner:	Alcohol
Product life:	(Well Stored) 5 years
Recoating:	After 10'
Heat resistance:	n/a
Condition for application:	T° min 8°C
	T° surface 5°C-50°C
	Humidity max. 85% R.H.P

\*The adhesion tests were done on PP (EPDM modified). Last rev ew's date: 2/01/2017.

### CAUTION



### APPARENCE



### LABEL



EX014PR0914 EPS Primer

### CAP SYSTEM



### PACKAGING

Nominal capacity: 400 ml.  
Heat resistance of packaging: <50°C  
Propellant: GLP – HC C<sub>3</sub>-C<sub>4</sub>

Box (6 units)  
205 X 140 X 200 mm.

