

Product information | TECHNICAL DATA SHEET

REFLECTIVE PAINT

400 ml, 13 Oz, 370 g.

GENERAL DESCRIPTION

Permanent reflective paint for a multitude of surfaces. In the dark, this product reflects light that is shone onto its surface. Grey finish.

FEATURES

- Highly reflective.
- Great durability.
- Does not contain lead nor other heavy metals.
- Easy to apply and repaint.
- Fast drying.

APPLICATIONS

This product can be applied on metallic, plastic, glass, wood and stone surfaces, or on any surface where a permanent reflective marking is required.

- Road signage
- Reflective symbols and markings
- onstruction areas
- DIY

INSTRUCTIONS FOR USE

- Clean the surface of dust and grease residue.
- Shake well before use, one or two minutes after hearing the sound of mixer.
- Aplicar a una distancia de 15-25 cm sin permitir la acumulación excesiva de producto. El producto sedimenta y padece una deshomogeneización de forma rápida, por este motivo es necesario la agitación del producto durante la aplicación del mismo.
- Apply as a single coat until a uniform layer of the product is applied.
- Reverse the aerosol valve to purge after use, if the actuator gets blocked, replace it with a new one.
- Do not apply any protective varnish on top of the product as it may alter the reflective characteristic
- The reflective effect will only be perceived by an observer who is standing directly in front of the object and shining light onto it.
- Don't spray on plugged equipments and use it only in well ventilated areas.
- Ask for MSDS.

PHYSICAL PROPERTIES

Type of liant:	Special resin
Color:	Grey
Dry to the touch (ASTM D-1640 ISO 1517):	10-15'
Completely dry (ASTM D-1640 ISO 1517):	24-48 h
VOC's	See safety sheet
Theoretical yield (continuous painting):	To be determined
Thinner:	Mixture of solvents
Product life:	>5 years
Condiciones de aplicación:	Minimum ambient temperature 8°C
	Surface temperature from 5°C a 50°C
	Max. humidity 85% R.H.P

Last date of revision: 30/10/2017

APPARENCE



LABEL



Reflective paint

CAP SYSTEM



PACKAGING

Nominal capacity: 150 ml.
Resistance to heat: <50°C
Propellant: DME

Box (6 units)
168 X 110,5 X 158 mm.



CAUTION

